





Quick installation guide






Turn power off before installation. All work should be done according to appropriate electrical codes.

Dimensions




| Product | Dimensions in mm | | | | | |
|--|------------------|-----------|---------------|---------------|---------|--|
| | Length (A) | Width (B) | Height 1 (C1) | Height 2 (C2) | Weight | |
| GreenPower LED interlighting module DR/B (deep red/blue) | 2491 | 48 | 76 | 33.8 | 3.57 kg | |
| GreenPower LED interlighting module mounting bracket | 89 | 50 | 140 | | | |
| GreenPower LED interlighting module mounting bracket Gen 2 EOL | 53 | 2 | 140 | | | |

Installation




December 2015

Installation of a fixed system




The "none IP rated area", must be build into an >IP66 environment. E.g. into a water tight junction box or water tight connectors.



For protection against electrical shock in case of a fault connect green/yellow wire to an external protective conductor. Be sure the driver is after installation on top of the module. For more detailed information about the electrical connection please check the Application Guide.

Max inputvoltage: 200 V-300 V 0-phase & 200-400 VAC between phases.

Ordering data and specifications Philips GreenPower LED interlighting



| Lamp type | Photon flux | Useful life time | Photon flux maintenance | Ingress | Energy consumption |
|--|-------------|------------------|-------------------------|-------------------|--------------------|
| | [µmol/s] | hours | ambient 25 °C | protection rating | W |
| GreenPower LED interlighting module DR/B (deep red/blue) | 220 | 25,000 | 90% | IP66 | 105 |

 $^{^{}st}$ The values for service life and photon flux maintenance are valid for an ambient temperature of 25 $^{\circ}$ C.

| Product | Order code |
|--|----------------|
| | 12 NC |
| GreenPower LED interlighting module DR/B (deep red/blue) | 9290 008 70106 |
| GreenPower LED interlighting module mounting bracket | 9290 008 80406 |
| GreenPower LED interlighting mounting bracket EOL | 9290 015 06206 |

© Philips Lighting Holding B.V. 2016. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Document order number: 3222 635 69710 V1

12/2015

Data subject to change.

For more information about Philips Horticulture LED Solutions visit: www.philips.com/horti

Write us an e-mail: horti.info@philips.com

Or tweet us: @PhilipsHorti