


MASTER TL5 HO Secura

Shatterfree fluorescent lighting. This TL5 High Output Secura lamp (tube diameter 16 mm) has a protective coating that keeps glass and lamp components together in the event of accidental breakage. The lamp is easily identifiable by a blue ring at one end. Application areas are all places where glass shatters can disturb operations and can have an impact on product and people safety, e.g. the food and beverage industry.

- Benefits:**
- Special protective coating around the lamp prevents products from contamination in case of accidental lamp breakage
 - High temperature-resistance (up to 200 °C) and no degradation under influence of temperature or UV
- Features:**
- Protective coating around the lamp
 - Fully compliant with IEC 61549 – Fragment Retention Lamp Standard
 - Superior coating material (Teflon) with high temperature resistance (up to 200 °C) and no degradation under influence of temperature or UV
 - Single blue ring around one end for identification
 - Direct retrofit for all TL5 HO lamps
- Application:**
- For use where contamination resulting from lamp breakage must be prevented, e.g. in food industry, suppliers to the food industry, health care, pharmaceuticals, cleanrooms etc.
 - Suitable for use in environments with increased risk of breakage, e.g. sports halls



Product ID	A max.	B max.	C max.	D max.
49W	1449.0	1456.1	1463.2	17
54W	1149.0	1156.1	1163.2	17

Dimensions in mm

MASTER TL5 High Output Secura

Shortcode	Wattage (W)	Cap Base	Luminous Flux Lamp (35°, lm)	Average Lifetime (hrs)	Colour Rendering Index (Ra)	Colour Temperature (K)	Min Order Quantity	Carton Quantity
TL549W840SECURA	49	G5	4900	30000	85	4000	40	40
TL554W840SECURA	54	G5	5000	30000	85	4000	40	40