

A close-up, profile view of a woman with long brown hair, wearing a bright yellow sweater. She is smiling and looking out a window, with her hand resting on a light-colored fabric. The background is softly blurred, showing a window with light coming through.

PHILIPS

LEDlamps

The complete portfolio



LED can
work for you

Professional LEDlamps catalogue

Content

Professional LEDlamps

LEDspot	4	AR111 - Put design in the spotlights	43
LEDcapsule	16	DimTone - The more you dim, the warmer the light	43
LEDbulb	20	LEDtube - The right LEDtube every time	44
LEDcandle	24	CRI90 - Spot on for colour enhancement	45
LEDluster	28	Value range - Quality, Value and lifetime	45
LED PL-C	32	High Performance Dimming	46
LEDtube	36	TransforMax	46
		Photometric diagrams	47



LEDspot



MASTER LEDspot			MASTER LEDspot Value	CorePro LEDspot
 	 			
MV GU10 / 4-35 W Page 6	MV GU10 / 4-35 W Page 7	MV GU10 / 3.5-35 W Page 8	MV GU10 / 3.5-35 W Page 9	
 	 			
MV GU10 / 4.5-50 W Page 6	MV GU10 / 5.4-50 W Page 7	MV GU10 / 4.3-50 W Page 8	MV GU10 / 5-50 W Page 9	
 				
LV MR16 GU5.3 / 6.5-35 W Page 10	LV MR16 GU5.3 / 7-35 W Page 10	LV MR16 GU5.3 / 8-50 W Page 10	LV MR16 GU5.3 / 3.4-20 W Page 11	MV R50 E14 / 4.5-40 W Page 15
				
LV MR11 GU4 / 3.5 W Page 12	LV MR16 GU5.3 / 6.3-35 W Page 11			
 	 			
LV AR111 G53 / 11-50 W Page 13	LV AR111 G53 / 15-75 W Page 13	LV AR111 G53 / 20-100 W Page 13		
				
MV PAR20 E27 / 5.5-50 W Page 14	MV PAR30S E27 / 9.5-75 W Page 14	MV PAR30S E27 / 9.5-90 W Page 14		
				
MV PAR38 E27 / 13-100 W Page 15				



MASTER LEDspot MV

With our LEDspots Mains Voltage you can enjoy bright, energising light, at the same time as saving energy and money. Perfect for accent and general lighting. With DimTone the light gets warmer when dimmed. CRI90 gives you the best colour presentation (for retail applications).

- CRI90 - see page 45
- DimTone: the more you dim the warmer the light - see page 43
- High Performance Dimming - see page 46
- Longest lifetime
- Superior light quality
- Maximum energy savings
- Delivers committed lifetime in application



MASTER LEDspot MV DimTone / 4-35 W



2700 - 2200
 GU10
 DIMMABLE
 50,000 H
 EEL
 10 PACK
 BEAM ANGLE 25° 40°
 DIMENSIONS 55 150
 89%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
DimTone 4-35W GU10 25D	4	35	280	70	1000	25	80	2700-2200	43828200
DimTone 4-35W GU10 40D	4	35	280	70	600	40	80	2700-2200	43830500



MASTER LEDspot MV DimTone / 4.5-50 W



2700 - 2200
 GU10
 DIMMABLE
 50,000 H
 EEL
 10 PACK
 BEAM ANGLE 25° 40°
 DIMENSIONS 55 150
 91%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
DimTone 4.5-50W GU10 25D	4.5	50	355	79	1400	25	80	2700-2200	43840400
DimTone 4.5-50W GU10 40D	4.5	50	355	79	800	40	80	2700-2200	43842800



MASTER LEDspot MV / 4-35 W / CRI 90



2700 / 3000 / 4000
 GU10
 DIMMABLE
 50,000 H
 EEL
 10 PACK
 BEAM ANGLE 25° 40°
 DIMENSIONS 57 150
 89%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
D 4-35W GU10 927 25D	4	35	250	63	925	25	90	2700	45727600
D 4-35W GU10 930 25D	4	35	260	65	962	25	90	3000	45731300
D 4-35W GU10 940 25D	4	35	282	71	1040	25	90	4000	45735100
D 4-35W GU10 927 40D	4	35	262	66	560	40	90	2700	45729000
D 4-35W GU10 930 40D	4	35	272	68	582	40	90	3000	45733700
D 4-35W GU10 940 40D	4	35	285	71	624	40	90	4000	45739900



MASTER LEDspot MV / 5.4-50 W / CRI 90



2700 / 3000 / 4000
 GU10
 DIMMABLE
 50,000 H
 EEL
 10 PACK
 BEAM ANGLE 25° 40°
 DIMENSIONS 57 150
 89%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
D 5.4-50W GU10 927 25D	5.4	50	360	80	1350	25	90	2700	45715300
D 5.4-50W GU10 930 25D	5.4	50	360	80	1350	25	90	3000	45719100
D 5.4-50W GU10 927 40D	5.4	50	378	84	800	40	90	2700	45717700
D 5.4-50W GU10 930 40D	5.4	50	378	84	800	40	90	3000	45721400
D 5.4-50W GU10 940 40D	5.4	50	392	87	830	40	90	4000	45725200

Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps and about transformer compatibility.



MASTER LEDspot MV Value

Quality, VALUE and lifetime

You've got it in one with the new range of MASTER LEDspot Value lamps. Designed with a 25D and 40D beam angle for general lighting applications in retail and hospitality, they offer high quality at an affordable price. With a choice of three colour temperatures, dimmable options, and a reliable lifetime, it's everything you value in LED.

- MASTER Value range - see page 45
- High Performance Dimming - see page 46
- Long lifetime
- Superior light quality
- Maximum energy savings



MASTER LEDspot MV Value / 3.5-35 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV Value	W	W	lm	lm/W	cd	°		K	8718696
D 3.5-35W GU10 827 25D	3.5	35	260	74	1000	25	80	2700	43832900
D 3.5-35W GU10 830 25D	3.5	35	270	77	1000	25	80	3000	43834300
D 3.5-35W GU10 840 25D	3.5	35	290	83	1000	25	80	4000	43836700
D 3.5-35W GU10 827 40D	3.5	35	260	74	600	40	80	2700	45703000
D 3.5-35W GU10 830 40D	3.5	35	270	77	600	40	80	3000	45705400
D 3.5-35W GU10 840 40D	3.5	35	290	83	600	40	80	4000	45707800



MASTER LEDspot MV Value / 4.3-50 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV Value	W	W	lm	lm/W	cd	°		K	8718696
D 4.3-50W GU10 827 25D	4.3	50	355	83	1400	25	80	2700	43838100
D 4.3-50W GU10 830 25D	4.3	50	365	85	1400	25	80	3000	43844200
D 4.3-50W GU10 840 25D	4.3	50	390	91	1400	25	80	4000	43846600
D 4.3-50W GU10 827 40D	4.3	50	355	83	800	40	80	2700	45709200
D 4.3-50W GU10 830 40D	4.3	50	365	85	800	40	80	3000	45711500
D 4.3-50W GU10 840 40D	4.3	50	390	91	800	40	80	4000	45713900



CorePro LEDspot MV

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light.

- Easy retrofit
- Long lifetime
- Huge energy saving
- Low heat generation



CorePro LEDspot MV / 3.5-35 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
3.5-35W GU10 827 36D	3.5	35	250	71	650	36	80	2700	48594100
3.5-35W GU10 830 36D	3.5	35	250	71	650	36	80	3000	48596500



CorePro LEDspot MV 5-50 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
5-50W GU10 827 36D	5	50	390	70	900	36	80	2700	48598900
5-50W GU10 830 50D	5	50	390	70	900	36	80	3000	48600900
5-50W GU10 840 36D	5	50	370	74	900	36	80	4000	49714200



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps and about transformer compatibility.



MASTER LEDspot LV MR16

The robustly designed MASTER LEDspot offers a choice of beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.)

- AirFlux
- TransforMax (excluding 20 W) – see page 46
- DimTone: the more you dim the warmer the light – see page 43
- Dimmable
- Long lifetime
- Compatible with most commonly available halogen transformers. Exclusively suited for electronic transformers



MASTER LEDspot LV MR16 / 6.5-35 W DimTone



2700-2200 GU5.3 DIMMABLE 25,000 H EEL 10 PACK BEAM ANGLE 24° 36° DIMENSIONS 50 51 81%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	8718969
6.5-35W 2700K MR16 24D	6.5	35	370	57	1800	24	80	2700-2200	44213500
6.5-35W 2700K MR16 36D	6.5	35	370	57	900	36	80	2700-2200	44215900



MASTER LEDspot LV MR16 / 7-35 W



2700 / 3000 / 4000 GU5.3 DIMMABLE 40,000 H EEL 10 PACK BEAM ANGLE 24° 36° 60° DIMENSIONS 51 51 80%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	8718696
D 7-35W 827 MR16 24D	7	35	390	60	2100	24	80	2700	48878200
D 7-35W 830 MR16 24D	7	35	410	63	2200	24	80	3000	48935200
D 7-35W 840 MR16 24D	7	35	430	66	2300	24	80	4000	48937600
D 7-35W 827 MR16 36D	7	35	385	60	1150	36	80	2700	48939000
D 7-35W 830 MR16 36D	7	35	405	63	1200	36	80	3000	48941300
D 7-35W 840 MR16 36D	7	35	425	66	1250	36	80	4000	48943700
D 7-35W 827 MR16 60D	7	35	360	60	440	60	80	2700	48945100
D 7-35W 830 MR16 60D	7	35	380	63	460	60	80	3000	48947500



MASTER LEDspot LV MR16 / 8-50 W



2700 / 3000 GU5.3 DIMMABLE 40,000 H EEL 10 PACK BEAM ANGLE 24° 36° DIMENSIONS 55 51 84%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	8718694	8718695
D 8-50W 827 MR16 24D	8	50	621	78	3100	24	80	2700	48999400	
D 8-50W 830 MR16 24D	8	50	621	78	3250	24	80	3000	49001300	
D 8-50W 827 MR16 36D	8	50	635	79	1650	36	80	2700		51536500
D 8-50W 830 MR16 36D	8	50	660	83	1700	36	80	3000		51538900



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps and about transformer compatibility.



MASTER LEDspot LV Value MR16

Quality, VALUE and lifetime

You've got it in one with the new range of MASTER LEDspot Value lamps. Designed with a 24D beam angle for general lighting applications in retail and hospitality, they offer high quality at an affordable price. With a choice of three colour temperatures, dimmable options, and a reliable lifetime, it's everything you value in LED.

- AirFlux
- TransforMax (excluding 20 W) – see page 46
- Dimmable
- Long lifetime
- Compatible with most commonly available halogen transformers. Exclusively suited for electronic transformers



MASTER LEDspot LV Value MR16 / 3.4-20 W



2700 / 3000 GU5.3 NON-DIMMABLE 25,000 H EEL 10 PACK BEAM ANGLE 24° 36° DIMENSIONS 54 50 83%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV Value	W	W	lm	lm/W	cd	°		K	8718696
3.4-20W 827 MR16 24D	3.4	20	220	65	1000	24	80	2700	47570600
3.4-20W 830 MR16 24D	3.4	20	225	66	1000	24	80	3000	47576800
3.4-20W 827 MR16 36D	3.4	20	220	65	550	36	80	2700	47572000
3.4-20W 830 MR16 36D	3.4	20	225	66	600	36	80	3000	47574400



MASTER LEDspot LV Value MR16 / 6.3-35 W



2700 / 3000 / 4000 GU5.3 DIMMABLE 25,000 H EEL 10 PACK BEAM ANGLE 24° 36° DIMENSIONS 51 51 82%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV Value	W	W	lm	lm/W	cd	°		K	8718696
D 6.3-35W 827 MR16 24D	6.3	35	380	60	1800	24	80	2700	49021100
D 6.3-35W 830 MR16 24D	6.3	35	395	63	1800	24	80	3000	49023500
D 6.3-35W 840 MR16 24D	6.3	35	410	65	1800	24	80	4000	49025900
D 6.3-35W 827 MR16 36D	6.3	35	380	60	980	36	80	2700	49027300
D 6.3-35W 830 MR16 36D	6.3	35	395	63	1000	36	80	3000	49029700
D 6.3-35W 840 MR16 36D	6.3	35	410	65	1000	36	80	4000	49031000



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps and about transformer compatibility.



MASTER LEDspot LV MR11

The MR11 spot truly enhances the presentation of silver jewellery, adding sparkle to the items on display.

- TransforMax - see page 46
- Long lifetime
- Clearly defined beam spread
- Compatible with most commonly available halogen transformers. Exclusively suited for electronic transformers



MASTER LEDspot LV MR11 / 3.5-20 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	8718696
3.5-20W GU4 2700K 24D	3.5	20	200	57	1000	24	80	2700	41019600



MASTER LEDspot LV AR111

With an elegant new design, MASTER LEDspot LV AR111 creates a brilliant visual effect for retail and hospitality applications like shops, showrooms and galleries. The high quality light brings out the true colours in merchandise, including reds. With excellent rendering of CRI90 and R9>50, colours stay vibrant and natural, enhancing the appeal of everything on display.

- TransforMax - see page 46
- Dimmable
- High quality of light
- Unique lens design



MASTER LEDspot LV AR111 / 11-50 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	871869651
D 11-50W 927 AR111 24D	11	50	560	51	2900	24	90	2700	488700
D 11-50W 930 AR111 24D	10	50	580	53	3000	24	90	3000	490000
D 11-50W 927 AR111 40D	10	50	550	50	1100	40	90	2700	492400
D 11-50W 930 AR111 40D	10	50	570	52	1150	40	90	3000	494800



MASTER LEDspot LV AR111 / 15-75 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	871869651
D 15-75W 927 AR111 24D	15	75	760	50	3900	24	90	2700	496200
D 15-75W 930 AR111 24D	15	75	770	51	4000	24	90	3000	498600
D 15-75W 927 AR111 40D	15	75	750	50	1400	40	90	2700	500600
D 15-75W 930 AR111 40D	15	75	760	50	1450	40	90	3000	502000



MASTER LEDspot LV AR111 / 20-100 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot LV	W	W	lm	lm/W	cd	°		K	871869651
D 20-100W 827 AR111 24D	20	100	1180	59	5800	24	80	2700	504400



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps and about transformer compatibility.



MASTER LEDspot MV PAR

With our LEDspots Mains Voltage you can enjoy bright, energising light, at the same time as saving energy and money. Perfect for task lighting.

- AirFlux
- Longest lifetime
- For accent and general lighting
- Superior light quality
- Maximum energy savings
- New and improved design



MASTER LEDspot MV PAR / 5.5-50 W PAR20

airflux TECHNOLOGY

2700 / 3000 / 4000 E27 DIMMABLE 45,000 H EEL A+ A++ 4000 K / 25D 6 PACK BEAM ANGLE 25° 40° DIMENSIONS 85.2 x 65 H 89%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
D 5.5-50W 2700K PAR20 25D	5.5	50	480	87	2000	25	80	2700	46063400
D 5.5-50W 3000K PAR20 25D	5.5	50	490	89	2050	25	80	3000	46065800
D 5.5-50W 4000K PAR20 25D	5.5	50	520	94	2150	25	80	4000	46067200
D 5.5-50W 2700K PAR20 40D	5.5	50	480	87	950	40	80	2700	46069600
D 5.5-50W 3000K PAR20 40D	5.5	50	490	89	970	40	80	3000	46071900
D 5.5-50W 4000K PAR20 40D	5.5	50	520	94	1000	40	80	4000	46073300



MASTER LEDspot MV PAR / 9.5-75 W PAR30S

airflux TECHNOLOGY

2700 / 4000 E27 DIMMABLE 40,000 H EEL A+ 6 PACK BEAM ANGLE 25° DIMENSIONS 94 x 92 H 87%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718291
D 9.5-75W 2700K PAR30S 25D	9.5	75	650	68	3500	25	80	2700	71434700
D 9.5-75W 4000K PAR30S 25D	9.5	75	750	79	3850	25	80	4000	71436100



MASTER LEDspot MV PAR / 9.5-90 W PAR30S

airflux TECHNOLOGY

2700 / 4000 E27 DIMMABLE 40,000 H EEL A+ 6 PACK BEAM ANGLE 25° DIMENSIONS 93 x 92 H 89%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
D 9.5-90W 827 PAR30S 25D SO	9.5	90	815	86	3500	25	80	2700	55080900
D 9.5-90W 840 PAR30S 25D SO	9.5	90	875	92	3850	25	80	4000	55082300

Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps.



MASTER LEDspot MV PAR / 13-100 W PAR38

airflux TECHNOLOGY

2700 E27 DIMMABLE 40,000 H (indoor) 20,000 H (outdoor) EEL A+ 6 PACK BEAM ANGLE 25° DIMENSIONS 132 x 124 H 87%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
MASTER LEDspot MV	W	W	lm	lm/W	cd	°		K	8718696
D 13-100W 2700K PAR38 25D	13	100	1000	62	5000	25	80	2700	46043600



CorePro LEDspot MV R50

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light.

- Easy retrofit
- Long lifetime
- Huge energy saving
- Low heat generation



CorePro LEDspot MV R50 / 4.5-40 W

airflux TECHNOLOGY

2700 E14 DIMMABLE 15,000 H EEL A+ 10 PACK BEAM ANGLE 36° DIMENSIONS 85 x 51 H 89%

Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro LEDspot R50	W	W	lm	lm/W	cd	°		K	8718291
4.5-40W E14 2700K 36D	4.5	40	255	57	650	36	80	2700	77017600

LEDcapsule & Specials

CorePro LEDcapsule & Specials



G4 / LV 1.2-10 W
Page 18




G4 / LV 2-20 W
Page 18



G9 / MV 2.5-25 W
Page 18



R7S / 6.5-60 W
Page 19



CorePro LEDcapsule

Our LEDcapsule provides crisp, sparkling halogen like light. It is especially suitable for task lighting and decorative applications.

- Long lifetime
- UV- and IR-free light for less heat and protection
- For heat-sensitive objects
- Unique sparkling effect



CorePro LEDcapsule LV / 1.2-10 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro LEDcapsule LV	W	W	lm	lm/W	cd	°		K	8718696
G4 3000K 1.2-10 W	1.2	10	105	88	-	n.a.	80	3000	42228100



CorePro LEDcapsule LV / 2-20 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro LEDcapsule LV	W	W	lm	lm/W	cd	°		K	8718696
G4 3000K 2-20 W	2	20	200	91	-	n.a.	80	3000	41916800



CorePro LEDcapsule MV / 2.5-25 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro LEDcapsule MV	W	W	lm	lm/W	cd	°		K	8718696
G9 2700K 2.5-25 W	2.5	25	204	82	-	n.a.	80	2700	41920500



Please refer to the site www.philips.com/masterledlamps for the latest information about transformer compatibility.



CorePro Specials R7S

- Low energy consumption
- Long lifetime compared to halogen
- The ideal solution for retrofitting decorative luminaires in retail and hospitality applications



CorePro LEDLinear R7S / 6.5-60 W



Product type	LED	Traditional	Lumen output	Efficacy	Beam intensity	Beam angle	CRI	Colour temperature	EOC
CorePro	W	W	lm	lm/W	cd	°		K	8718696
LEDLinear R7S 117mm 6.5-60W 830	6.5	60	806	124	-	300	80	3000	52253000



LEDbulb

MASTER LEDbulb DimTone		CorePro LEDbulb			
					
E27/B22 / 6-40 W Clear Page 22	E27/B22 / 9-60 W Clear Page 22	E27/B22 / 6-40 W Page 23	E27/B22 / 9-60 W Page 23	E27/B22 / 11-75 W Page 23	E27/B22 / 13.5-100 W Page 23



MASTER LEDbulb

The MASTER LEDbulb range delivers a dimmable warm light effect for a welcoming, warm atmosphere, making it ideal for general lighting applications. With DimTone the light gets warmer when dimmed which is especially suited for hospitality applications.

- DimTone: the more you dim the warmer the light - see page 43
- High Performance Dimming - see page 46
- Longest lifetime
- Superior light quality
- Maximum energy savings



MASTER LEDbulb clear / 6-40 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDbulb clear	W	W	lm	lm/W			K	8718696
DT 6-40W E27 A60 CL	6	40	470	77	A60	80	2700 - 2200	48128800
DT 6-40W B22 A60 CL	6	40	470	77	A60	80	2700 - 2200	48130100



MASTER LEDbulb clear / 9-60 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDbulb clear	W	W	lm	lm/W			K	8718696
DT 9-60W E27 A60 CL	9	60	806	89	A60	80	2700 - 2200	48132500
DT 9-60W B22 A60 CL	9	60	806	89	A60	80	2700 - 2200	48134900



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps.



CorePro LEDbulb

CorePro LEDbulbs are designed for retrofit replacements of incandescent bulbs, and are compatible with existing fixtures with E27 or B22 holders.

- Easy retrofit
- Long lifetime
- Huge energy saving
- Low heat generation




CorePro LEDbulb / 6-40 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDbulb	W	W	lm	lm/W			K	8718696
6-40W 827 E27	6	40	470	78	A60	80	2700	49080800
6-40W 827 B22	6	40	470	78	A60	80	2700	51008700
6-40W 840 E27	6	40	470	78	A60	80	4000	51036000




CorePro LEDbulb / 9-60 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDbulb	W	W	lm	lm/W			K	8718696
9-60W 827 E27	9	60	806	90	A60	80	2700	49078500
9-60W 827 B22	9	60	806	90	A60	80	2700	51006300



CorePro LEDbulb / 11-75 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDbulb	W	W	lm	lm/W			K	8718696
11-75W 827 E27	11	75	1055	96	A60	80	2700	49076100
11-75W 827 B22	11	75	1055	96	A60	80	2700	51004900
10-75W 840 E27	10	75	1055	106	A60	80	4000	51032200



CorePro LEDbulb / 13.5-100 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDbulb	W	W	lm	lm/W			K	8718696
13.5-100W 827 E27	13.5	100	1521	112	A60	80	2700	49074700
13.5-100W 827 B22	13.5	100	1521	112	A60	80	2700	51002500

LEDcandle



MASTER LEDcandle DimTone



E14 / 4-25 W
Page 26



E14 / 4-25 W
Page 26

DiamondSpark



B15 / 6-40 W
Page 27



E14 / 6-40 W
Page 26



E14 / 6-40 W
Page 26

CorePro LEDcandle



E27 / 6-40 W
Page 26




E14 / 5.5-40 W
Page 27



E14 / 4-25 W
Page 27



E14 / 5.5-40 W
Page 27



MASTER LEDcandle

Thanks to a revolutionary new lens design, these candles now produce the most beautiful sparkling light. The ivory-coloured design is a perfect match with existing luminaires.

- DimTone: the more you dim the warmer the light - see page 43
- Unique, eye-catching lens design
- Huge energy savings



MASTER LEDcandle DimTone / 4-25 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDcandle	W	W	lm	lm/W			K	8718696
DT 4-25W E14 827 B38 CL	4	25	250	65	B38	80	2700-2200	45368100
DT 4-25W E14 827 BA38 CL	4	25	250	65	BA38	80	2700-2200	45376600



MASTER LEDcandle DimTone / 6-40 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDcandle	W	W	lm	lm/W			K	8718696
DT 6-40W E14 827 B38 CL	6	40	470	78	B38	80	2700-2200	45350600
DT 6-40W E14 827 BA38 CL	6	40	470	78	BA38	80	2700-2200	45354400



MASTER LEDcandle DimTone / 6-40 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDcandle	W	W	lm	lm/W			K	8718696
DT 6-40W B22 827 B38 CL	6	40	470	78	B38	80	2700-2200	45362900
DT 6-40W E27 827 B38 CL	6	40	470	78	B38	80	2700-2200	47479200



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps.



MASTER LEDcandle DiamondSpark / 6-40 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDcandle	W	W	lm	lm/W			K	8718696
DT 6-40W B15 827 B38 CL	6	40	470	78	B39	80	2700	179346500



CorePro LEDcandle

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps.

- Non-Dimmable
- Clear and frosted
- Huge energy savings



CorePro LEDcandle clear / 4-25 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDcandle	W	W	lm	lm/W			K	8718696
ND 4-25W E14 827 B35 CL	4	25	250	65	B35	80	2700	50757500



CorePro LEDcandle clear / 5.5-40 W



Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDcandle	W	W	lm	lm/W			K	8718696
ND 5.5-40W E14 827 B35 CL	5.5	40	470	85	B35	80	2700	45479400

LEDluster

MASTER LEDluster DimTone		CorePro LEDluster	
			
E14 / 4-25 W Page 30	E14 / 6-40 W Page 30	E14 / 4-25 W Page 31	E14 / 5.5-40 W Page 31
			
B22 / 6-40 W Page 30			



MASTER LEDluster

Thanks to a revolutionary new lens design, these lusters now produce the most beautiful sparkling light. The ivory-coloured design is a perfect match with existing luminaires.

- DimTone: the more you dim the warmer the light - see page 43
- Unique, eye-catching lens design
- Huge energy savings



MASTER LEDluster DimTone / 4-25 W

DimTone
 2700 - 2200
 E14
 DIMMABLE
 25,000 H
 A+
 10 PACK
 DIMENSIONS 95 | 48 |
 84%

Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDluster	W	W	lm	lm/W			K	8718696
DT 4-25W E14 827 P48 CL	4	25	250	63	P48	80	2700-2200	45378000



MASTER LEDluster DimTone / 6-40 W

DimTone
 2700 - 2200
 E14
 DIMMABLE
 25,000 H
 A+
 10 PACK
 DIMENSIONS 95 | 48 |
 85%

Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDluster	W	W	lm	lm/W			K	8718696
DT 6-40W E14 827 P48 CL	6	40	470	78	P48	80	2700-2200	45358200



MASTER LEDluster DimTone / 6-40 W

DimTone
 2700 - 2200
 B22
 DIMMABLE
 25,000 H
 A+
 10 PACK
 DIMENSIONS 95 | 48 |
 85%

Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
MASTER LEDluster	W	W	lm	lm/W			K	8718696
DT 6-40W B22 827 B38 CL	6	40	470	78	B38	80	2700-2200	47477800



Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps.



CorePro LEDluster

The CorePro LEDluster is designed for retrofit replacement of incandescent lamps.

- Non-Dimmable
- Huge energy savings



CorePro LEDluster clear / 4-25 W

2700
 E14
 E27
 NON-DIMMABLE
 15,000 H
 A+
 10 PACK
 DIMENSIONS E14 88 | 45 |
 DIMENSIONS E27 95 | 48 |
 84%

Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDluster	W	W	lm	lm/W			K	8718696
ND 4-25W E14 827 P45 CL	4	25	250	65	P45	80	2700	50759900



CorePro LEDluster clear / 5.5-40 W


2700 / 4000
 E14
 E27
 NON-DIMMABLE
 15,000 H
 A+
 10 PACK
 DIMENSIONS E14 88 | 45 |
 DIMENSIONS E27 95 | 48 |
 86%

Product type	LED	Traditional	Lumen output	Efficacy	Bulb shape	CRI	Colour temperature	EOC
CorePro LEDluster	W	W	lm	lm/W			K	8718696
ND 5.5-40W E14 827 P45 CL	5.5	40	470	85	P45	80	2700	45483100

LED PL-C

CorePro LED PL-C

 NEW G24d-2	 NEW G24d-3	 NEW G24q-2	 NEW G24q-3
6.5 & 8.5 W 2-pin Page 34		6.5 & 9 W 4-pin Page 34	



CorePro LED PL-C

Downlighting in general circulation areas represents a major lighting cost for many buildings. CorePro LED PL-C is a retrofit LED PL-C lamp that delivers incredible energy savings over a 30,000 hours lifetime and requires less maintenance and servicing. So you can downsize your downlighting costs with energy efficient LED lamps.

- Up to 60% more efficient compared to fluorescent PL-C lamps, saving on energy costs.
- Lifetime up to 30,000 hours, reducing maintenance costs.
- Made of shatter-proof plastic instead of glass.
- Easy upgrade from current conventional downlight fixture.
- Re-using the existing fixture without major modifications, using a similar PL-C form-factor.
- Instant 100% light.
- No flickering or stroboscopic light.



CorePro LED PL-C / 6.5-8.5 W 2-pin



Product type	LED	Rotable	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC
CorePro LED PLC	W		lm		°		K	
6.5W 830 2P G24d-2	6.5	Yes	600	EM	120	80	3000	54127200
6.5W 840 2P G24d-2	6.5	Yes	650	EM	120	80	4000	54129600
8.5W 830 2P G24d-3	8.5	Yes	900	EM	120	80	3000	54123400
8.5W 840 2P G24d-3	8.5	Yes	950	EM	120	80	4000	54125800



CorePro LED PL-C / 6.5-9 W 4-pin



Product type	LED	Rotable	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC
CorePro LED PLC	W		lm		°		K	
6.5W 830 4P G24q-2	6.5	Yes	600	HF	120	80	3000	54119700
6.5W 840 4P G24q-2	6.5	Yes	650	HF	120	80	4000	54121000
9W 830 4P G24q-3	9	Yes	900	HF	120	80	3000	54115900
9W 840 4P G24q-3	9	Yes	950	HF	120	80	4000	54117300









Downsize your downlighting costs with LED



G24d-2 G24d-3 G24q-2 G24q-3

Philips CorePro LED PL-C is the first LED PL-C lamp to replace fluorescent alternatives with up to 60% energy savings and 30,000 hours lifetime. A retrofit lamp that's simple to install, fits all 2-pin (EM) and 4-pin (HF) fixtures and requires less maintenance and servicing. So you can downsize your downlighting costs with energy efficient LED.

LEDtube


MASTER LEDtube		CorePro LEDtube	
 EM	 HF	 Standard output	 CorePro
Standard output Page 40		Page 42	
 EM	 HF	 High output	
High Output Page 40			
 EM	 HF	 Ultra output	
Ultra Output Page 41			



Works with
Electro Magnetic ballast (EM)



Works with
High Frequency ballast (HF)



Standard output
1600-2000 lumen

- 1200 mm
- 1200 mm InstantFit
- 1500 mm
- 1500 mm InstantFit

High output
2100-3100 lumen

- 1200 mm
- 1200 mm InstantFit
- 1500 mm
- 1500 mm InstantFit

Ultra output
2500-3700 lumen

- 1200 mm
- 1200 mm InstantFit
- 1500 mm
- 1500 mm InstantFit




Rotating end-caps

To ensure maximum compatibility with existing luminaires, directional LEDtubes often need to be adjusted towards where light is needed most. That's why all Philips MASTER products have this feature as standard. It allows the LEDtube to be easily rotated up to 90 degrees, giving you the freedom to direct the light to best effect.


G13 MASTER LEDtube

Whatever you need, the Philips MASTER LEDtubes portfolio has it all. The Philips MASTER LEDtube portfolio exists out of three categories of light output – Standard, High and Ultra output. A simple change that will make it even easier to choose the right lamp, for the right application. From best energy efficiency to the best light output. A simple switch, our LEDtubes come in a choice of lengths and colour temperatures, with the option of rotating. So with Philips, you always have the right LEDtube every time.


InstantFit HF compatibility. No wires to replace, no hassle changing drivers; our InstantFit solution works with High Frequency electronic ballast, making it easy and safe for all installation methods. All you have to do is slot the tube into your existing fitting.




Product type	LED	Traditional	Rotatable endcap	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC 1 pcs (C)*	
EM MASTER LEDtube (EM)	W	W		lm		°		K	8718291	
1200mm	14.5	36	Yes	1600	EM & Mains	160	83	4000	79308300	
1200mm	14.5	36	Yes	1600	EM & Mains	160	83	6500	79310600	
1500mm	20	58	Yes	2000	EM & Mains	160	83	4000	73451200	
1500mm	20	58	Yes	2000	EM & Mains	160	83	6500	73453600	
HF MASTER LEDtube (HF)	W	W		lm		°		K	8718291	8718696
1200mm InstantFit	16.5	36	Yes	1600	HF	160	83	4000	72885600	
1200mm InstantFit	16.5	36	Yes	1600	HF	160	83	6500	72887000	
1500mm InstantFit	22	58	Yes	2000	HF	160	83	4000		40078400
1500mm InstantFit	22	58	Yes	2000	HF	160	83	6500		40080700



Product type	LED	Traditional	Rotatable endcap	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC 1 pcs (C)*	
EM MASTER LEDtube (EM)	W	W		lm		°		K	8718696	8718291
1200mm	18	36	Yes	1900	EM & Mains	160	83	3000	42198700	
1200mm	18	36	Yes	2100	EM & Mains	160	83	4000	42200700	
1200mm	18	36	Yes	2100	EM & Mains	160	83	6500	42202100	
1500mm	23	58	Yes	2900	EM & Mains	160	83	3000		78956700
1500mm	23	58	Yes	3100	EM & Mains	160	83	4000		78958100
1500mm	23	58	Yes	3100	EM & Mains	160	83	6500		78960400
HF MASTER LEDtube (HF)	W	W		lm		°		K	8718696	
1200mm InstantFit	18	36	Yes	2000	HF	160	83	3000	51456600	
1200mm InstantFit	18	36	Yes	2100	HF	160	83	4000	47125800	
1200mm InstantFit	18	36	Yes	2100	HF	160	83	6500	47127200	
1500mm InstantFit	25	58	Yes	2900	HF	160	83	3000	51458000	
1500mm InstantFit	25	58	Yes	3100	HF	160	83	4000	40886500	
1500mm InstantFit	25	58	Yes	3100	HF	160	83	6500	40888900	



Product type	LED	Traditional	Rotatable endcap	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC 1 pcs (C)*
EM MASTER LEDtube (EM)	W	W		lm		°		K	8718696
1200mm UO	20	36	Yes	2300	EM & Mains	150	83	3000	46149500
1200mm UO	20	36	Yes	2500	EM & Mains	150	83	4000	46151800
1200mm UO	20	36	Yes	2500	EM & Mains	150	83	6500	46155600
1500mm UO	25	58	Yes	3400	EM & Mains	150	83	3000	46157000
1500mm UO	25	58	Yes	3700	EM & Mains	150	83	4000	46159400
1500mm UO	25	58	Yes	3700	EM & Mains	150	83	6500	46163100
HF MASTER LEDtube (HF)	W	W		lm		°		K	8718696
1200mm UO	22	36	Yes	2300	HF	160	83	3000	55282700
1200mm UO	22	36	Yes	2500	HF	160	83	4000	55278000
1200mm UO	22	36	Yes	2500	HF	160	83	6500	55280300
1500mm UO	26	58	Yes	3400	HF	160	83	3000	55288900
1500mm UO	26	58	Yes	3700	HF	160	83	4000	55284100
1500mm UO	26	58	Yes	3700	HF	160	83	6500	55286500



Product type	LED	Traditional	Rotatable endcap	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC 1 pcs (C)*	
EM MASTER LEDtube (EM)	W	W		lm		°		K	8718696	8718291
600mm series	10	18	Yes	1000	EM & Mains	160	83	3000	46141900	
600mm series	10	18	Yes	1050	EM & Mains	160	83	4000	46143300	
600mm series	10	18	Yes	1050	EM & Mains	160	83	6500	46145700	
900mm RS *)	15	30	Yes	1575	EM & Mains	160	80	4000		23880500
900mm RN *)	15	30	Yes	1575	EM & Mains	160	80	4000	47121000	
900mm RS *)	15	30	Yes	1575	EM & Mains	160	80	6500		23882900
900mm RN *)	15	30	Yes	1575	EM & Mains	160	80	6500	47123400	
1800mm	25	70	Yes	3700	EM & Mains	160	85	4000	48037300	

Protection starter



Product type	EOC 10 pcs (I)
Accessory	8718291
Starter EMP	72928000

Please refer to the site www.philips.com/masterledlamps for the latest information about dimming MASTER LEDlamps and about transformer compatibility.


***) Note:** Some of the products are only available in specific countries. Product descriptions with 'RS' are only available in: France, Spain, Portugal, Italy, Greece and Israel. Product descriptions with 'RN' are only available in the rest of the European countries.



CorePro LEDtube

CorePro LEDtubes offer even better value. Thanks to the new glass housing they're even more affordable. Plus we've improved the energy consumption from 80 to 100 lm/W to make them even more efficient. A simple, retrofit replacement, the 600 mm and 1200 mm CorePro LEDtubes offer low energy consumption with instant savings. Perfect for basic applications that demand an affordable solution.

CorePro LEDtube




4000 / 6500 G13 NON-DIMMABLE FRAGILE 30,000 H 600 mm EEL BEAM ANGLE 140° BEAM ANGLE 240° DIMENSIONS 28 589 1198 1498

Product type	LED	Traditional	Lumen output	Operation	Beam angle	CRI	Colour temperature	EOC 1 pcs (C)*
CorePro LEDtube	W	W	lm		°		K	
600mm 9W840 C Glass	8	18	800	EM & Mains	240	80	4000	49277200
600mm 9W865 C Glass	8	18	800	EM & Mains	240	80	6500	49279600
1200mm 16W840 C Glass	16	36	1600	EM & Mains	240	80	6500	49281900
1200mm 16W865 C Glass	16	36	1600	EM & Mains	240	80	4000	49283300
1500mm 840	20	58	2000	EM & Mains	140	80	4000	42794100
1500mm 865	20	58	2000	EM & Mains	140	80	6500	42796500

*) incl. EMP

Protection starter



34.5 21.5 DIMENSIONS

Product type	EOC 10 pcs (I)
Accessory	8718291
Starter EMP	72928000

Philips MASTER LEDspot LV AR111

Put design in the spotlights

In shops, showrooms and galleries, but also in restaurants and hotels, people need to see colours as they are. Which makes Philips MASTER LEDspot LV AR111 lighting the perfect choice. With its high Colour Rendering Index of 90, enhanced red colour makes objective more vivid. Colours stay vibrant and natural.

With an elegant new design, MASTER LEDspot LV AR111 creates a brilliant visual effect for retail and hospitality applications like shops, showrooms and galleries. The high quality light brings out the true

colours in merchandise. With excellent rendering of CRI90, enhancing red, colours stay vibrant and natural on everything in retail and hospitality applications.



DimTone - The more you dim, the warmer the light



DimTone takes LEDlamp dimming to an exciting next level with a beautiful, sunset-like effect. As the light is dimmed, DimTone reduces the colour temperature from 2700 K down to 2200 K. This creates a warm, intimate ambience at lower light levels, with the same effect as dimmed halogens or incandescent lamps. So hotel, bar and restaurant owners can take advantage of energy-saving LED lighting and still create a natural, cosy ambience.



The right LEDtube every time



Standard output

High output

Ultra output

Whatever you need, the Philips MASTER LEDtube portfolio has it all. We've repositioned the way that our lamps are labelled into three new categories of light output – Standard, High and Ultra output. A simple change that will make it even easier to choose the right lamp, for the right application. From best energy efficiency to the best light output. A simple switch, our LEDtubes come in a choice of lengths and colour temperatures, with the option of rotating end-caps. So with Philips, you always have the right LEDtube every time.

Spot on for colour enhancement



With a high colour rendering index of 90, the MASTER LEDspot MV is the perfect halogen replacement for retail applications. The single optics outshine other lamps with high intensity, high quality light that brings out the true colours in merchandise for an extra-long lifetime of 50,000 hours. Choose 4-35 W or 5.4-50 W in three colour temperatures, all with high performance dimming and low energy consumption. So you can light up merchandise with LED.

Philips MASTER LEDspot

www.philips.com/masterledlamps

Quality, Value and lifetime



You've got it in one with the new range of MASTER LEDspot Value lamps. They offer high quality at an affordable price with a 25, 36 and 40 degree beam angle for general lighting applications. As a 20 W, 35 W or 50 W equivalent, with a choice of three colour temperatures, dimmable options and a 25,000 and 35,000 hour lifetime, these lamps are everything you value in LED.

Philips MASTER LEDspot Value

www.philips.com/masterledlamps

High Performance Dimming

Thanks to High Performance Dimming you will enjoy smooth, flicker-free dimming. MASTER LEDlamps have been tested with all the major dimmer brands in the market.

- Broad dimmer compatibility supporting a wide range of normal phase-cut dimmers: wall box dimmers, panels, plug-in unit phase-cut dimming
- High dimming performance: smooth dimming curve, deeper dimming level, one to multiple lamps

Note: To ensure high dimming performance with the MASTER LEDspot MV GU10 8 W these lamps should not be connected with other lamp types on the same dimmer ('mixed load').

TransforMax™ (patented)

First class halogen transformer compatibility thanks to intelligent electronics within low voltage LEDlamps.

Philips designed a unique (patent protected) intelligent driver concept for low voltage (12 V) LEDlamps, which enables broad compatibility with existing electronic and electromagnetic Halogen transformers. Therefore, Philips low voltage (12 V) LEDlamps universally replace 12 V Halogen spot lamps with unique first class transformer compatible electronics. This technology is called TransforMax™ which enables the lamp to work on most sockets – a simple 'plug & play' retrofit solution.


Without dimmer

20% of Transformer rating
(20% x 150 W = 30 W)

LED Wattage (7 W)

Branch Max (4.3)

4 lamps per transformer




Dimmer Rating
(300 W)

Transformer Wattage (150 W)

System Max (2)

2 transformers per dimmer




20% of Transformer rating
(20% x 150 W = 30 W)

LED Wattage (7 W)

Branch Max (4.3)

4 lamps per transformer



Note: Electronic Dimmers that cannot meet the loading rule will be specified in the dedicated application note (www.philips.com/masterledlamps).



Please refer to the site www.philips.com/masterledlamps for the latest information about transformer compatibility.


Photometric diagrams

This is a selection of the photometric diagram visualisations.

Please visit www.philips.com/masterledlamps for photometric .ies files of all current products.




MASTER LEDspot MV
Page 6



4-35W GU10 2700K 25D




CorePro LEDspot MV
Page 9



5-50W GU10 2700K 36D




MASTER LEDspot LV
Page 10



8-50W MR16 2700K 24D




MASTER LEDspot AR111
Page 13



15-75W AR111 2700K 40D




MASTER LEDspot MV PAR
Page 14



5.5-50W PAR 20 2700K 25D




CorePro LEDcapsule
Page 18



1.2-10W G4 2700K




CorePro LEDbulb
Page 23



6-40W E27 2700K




MASTER LEDcandle
DimTone
Page 26



6-40W E14 2700K




MASTER LEDtube
Ultra output
Page 40



18W G13 6500K



CorePro LEDtube
Page 41



10W G13 6500K

