

PHILIPS

Fortimo

LED system

Strip Gen3 102 mm
375 lm LV3



Datasheet


Fortimo LED Strip Gen3

Fortimo LED Strip systems are ideal for use in designer or miniaturized, slim linear luminaires for architectural applications, which were not previously possible with fluorescent lighting or Fortimo LED Line.

Key features and benefits

- State-of-the-art LED module efficiency of up to 165 lm/W
- Long life-time: >50,000 hours
- High color rendering (CRI >80 and >90)
- Excellent color consistency of 3 SDCM
- Variety of color temperatures (3000 K, 4000 K and 5000 K)
- Two lumen packages: 650 lm and 1100 lm per foot
- Tunable lumen output, efficacy and lifetime
- Wide case temperature (T_c) range from -40 °C to +80 °C
- Push-in connectors enabling automated wiring
- Five year system warranty

Suitable for:



Ordering data

Commercial product name	EOC	12NC
Fortimo LED Strip 102mm 375lm 830 LV3	8718291 788898 00	9290 009 00906
Fortimo LED Strip 102mm 375lm 840 LV3	8718291 788911 00	9290 009 01006

Drive currents and case temperatures

Parameter	Nominal*	Life**	Max***	Unit
I (current through the LED module)	82	90	90	mA
Tc (case temperature at Tc point)	50	55	80	°C

* Nominal value at which typical performance is specified.

** Value at which lifetime L70B50 ≥ 50,000 hour is specified.

*** Maximum value for safe operation; do not operate above this value.

Optical characteristics - table per CCT


Fortimo LED Strip 102 mm 375 lm 830 LV3

Parameter	Min	Typ	Max	Unit
Luminous flux	333	360	387	lm
Module efficiency	125	139	153	lm/W
Correlated color temperature (CCT)		3000		K
Color coordinates (CIEx, CIEy)		(0.435, 0.401)		-
CRI	80			-
Radiation angle		120		deg

Note: Specifications stated at Tc nom = 40 °C and I nom = 136 mA.
Color consistency of 3 SDCM.

Tolerance for flux data is ±7.5%.

Tolerance for efficacy data is ±10%.




Fortimo LED Strip 102 mm 375 lm 840 LV3

Parameter	Min	Typ	Max	Unit
Luminous flux	347	375	403	lm
Module efficiency	130	144	158	lm/W
Correlated color temperature (CCT)		4000		K
Color coordinates (CIEx, CIEy)		(0.381, 0.377)		-
CRI	80			-
Radiation angle		120		deg

Note: Specifications stated at Tc nom = 40 °C and I nom = 136 mA.
Color consistency of 3 SDCM.


Tolerance for flux data is ±7.5%.

Tolerance for efficacy data is ±10%.



Measurement tolerance is ± 2.5% for the flux data and 5% for the efficacy data.

Beam shape



The Philips Fortimo LED Line generates a Lambertian beam shape, which is a pragmatic starting point for OEMs wishing to design secondary optics.

Electrical characteristics

Parameter	Min	Typ	Max	Unit
Nominal current		82		mA
Forward voltage	29.9	31.8	32.9	V
Power consumption	2.5	2.6	2.7	W
Energy efficiency label		A++		
Minimum dimming for performance	10			%
Number of parallel modules per chain			12	
Bins		NA		

Note: Specifications stated at Tc nom = 50 °C and I nom = 82 mA.

Performance over life

Lumen maintenance

Operation point	Time x 1000 hours	L70			L80			L90		
		B50	B20	B10	B50	B20	B10	B50	B20	B10
80% I-nom 66 mA	Tc 25 °C	> 54	> 54	> 54	> 54	> 54	> 54	51	50	49
	Tc-nom 40 °C	> 54	> 54	> 54	> 54	> 54	> 54	29	29	28
	Tc-life 60 °C	52	50	49	32	31	31	15	15	15
I-nom 82 mA	Tc 25 °C	> 54	> 54	> 54	> 54	> 54	> 54	51	50	49
	Tc-nom 40 °C	> 54	> 54	> 54	> 54	> 54	> 54	29	29	28
	Tc-life 60 °C	52	50	49	32	31	31	15	15	15
I-life 90 mA	Tc 25 °C	> 54	> 54	> 54	> 54	> 54	> 54	51	50	49
	Tc-nom 40 °C	> 54	> 54	> 54	> 54	> 54	> 54	29	29	28
	Tc-life 60 °C	52	50	49	32	31	31	15	15	15

Values in the table are based on available LM80 LED data (9000h). Lumen maintenance will be updated once additional measurement data becomes available.

Parameter	Min	Typ	Max	Unit
$\Delta u'v'$ at 6000 hours			0.007	-

Specifications stated while Tc < Tc-life and I < I-life.

Abs max ratings

Parameter	Min	Typ	Max	Unit
Current I _{max}			90	mA
Case temperature T _c max			80	°C
ESD (direct contact)			8	kV
ESD (air)			15	kV
Ambient temperature	-40			°C

Wiring



Specification item	Value	Unit	Condition
Input wire cross-section	0.2...0.75	mm ²	Solid
	18...24	AWG	
	0.3...0.5	mm ²	Stranded
	20...22	AWG	
Input wire strip length	7.5...8.5	mm	
Tested cable length*	4000	mm	Total length of wiring including LED modules, one way

* Note: connector suited for robot wiring.

Mechanical characteristics

Parameter	Min	Typ	Max	Unit
Length	101.7	102.0	102.3	mm
Width	18.75	18.90	19.05	mm
Height excl. connector	1.72	1.87	2.02	mm
Height incl. connector	4.95	5.20	5.35	mm
Warpage (IPC-TM-650)			0.8	mm

Note: Bow & Twist of the PCB after production tested and released according IPC-TM-650 2.4.22.



Application information

Compliance and approval

IEC / EN 62031, IEC / EN 62471

Photobiological safety

Risk group: Exempt

Environmental

RoHS / REACH


Application information

IP rating	No IP rating
Overheating protection	No protection
Luminaire class	UL Class 2/ Class II or Class III

Warranted number of full thermal product cycles at which the survival rate of the population $\geq 90\%$, at 25 °C ambient temperature


Case temperature Tc [°C]	Amount of cycles
35	
40	14,600
45	
50	14,600
55	
60	14,600
65	
70	12,000
75	
80	8,000
85	
90	
95	

Tuning information



Flux and efficacy versus current

I [A]	Flux [%]	Efficacy [%]
0.090	110%	99%
0.082	100%	100%
0.073	90%	102%
0.064	80%	103%
0.056	70%	105%
0.047	60%	107%
0.039	50%	109%




Flux and efficacy versus temperature at Tc

I [A]	Flux [%]	Efficacy [%]
55	99%	100%
50	100%	100%
45	101%	101%
40	102%	101%
35	103%	102%
30	103%	102%
25	104%	103%
20	105%	103%
15	106%	104%
10	107%	104%
5	107%	105%
0	108%	105%

Lumen maintenance

Lumen maintenance: at I life and Tc life conditions


Fortimo LED Strip 102 mm 375 lm LV3



Lumen depreciation as a function of operating hours for LED Strip 102 mm 375 lm LV3.

Lumen maintenance (B50): at current I life

Fortimo LED Strip 102 mm 375 lm LV3



Lumen depreciation as a function of operating hours for LED Strip 102 mm 375 lm LV3 at different Tc values.



© 2015 Royal Philips N.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

06/2015
Data subject to change

www.philips.com/technology
www.philips.com/fortimo
www.philips.com/xitanium