

## High Pressure Sodium Lamp Ballast

Catalog Number 74P7903 For 70W S62 60 Hz R-PFC

## Status: Active DIMENSIONS AND DATA INPUT VOLTS 120 CIRCUIT TYPE R-PFC POWER FACTOR (min) 85% REGULATION Line Volts WITHIN TRAPEZOID Lamp Watts LINE CURRENT (Amps) Operating.... 12.8" 1.30 Starting..... UL TEMPERATURE RATINGS Insulation Class Coil Temperature Code 1029 MIN. AMBIENT STARTING TEMP. -40°F or -40°C NOM. OPEN CIRCUIT VOLTAGE 120 INPUT VOLTAGE AT LAMP DROPOUT..... 98 INPUT WATTS RECOMMENDED FUSE (Amps)..... MAX. CASE TEMP 90 °C NIPPLE 1/2" NPT-14 CORE and COIL Dimension (A) Dimension (B) Weight (lbs.) 5 Lead Lengths POSTLINE UNIT DIMENSIONS CAPACITOR REQUIREMENT Microfarads Volts (min.) Fault Current Withstand (amps) 60 Hz TEST PROCEDURES (Refer to Advance Test Procedure for HID Ballasts - Form 1270) High Potential Test (Volts) 1 minute 2000 2500 2 seconds Open Circuit Voltage Test (Volts) 108-132 Short-Circuit Current Test (Amps) Secondary Current Capacitor: Input Current..... Wiring Diagram: BLACK PHOTO\* CONTROL TO FIXTURE GREEN INPUT The capacitor is included as COM WHITE part of the potted assembly. Postline Wiring Diagram Ordering Information Order Suffix Description IN CAN 011P Thermally protected Ballast with kit Ignitor: 011P-XK Themally protected Ballast without kit The ignitor is included as part of the potted assembly. Ballast to Lamp Distance (BTL) = 10 feet Temp Rating: 90℃

Data is based upon tests performed by Advance Transformer in a controlled environment and representitive of relative performance.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.