

PHILIPS ADVANCE

LED Driver

Xitanium

300W 120-277V 0.10-1.50A
Programmable
929000712703



Long-lasting and low maintenance, LED-based light sources are an excellent solution for all lighting applications. For optimal performance, these solutions require reliable drivers matching the long lifetime of the LEDs. The Philips Advance Xitanium LED Outdoor Driver portfolio offers a range of products specially designed to operate LED solutions in outdoor applications. These drivers are designed for hard-wired integration into outdoor luminaires for rugged applications. They operate to specification under wide temperature and electrical ranges to help ensure reliability.


Specifications

Input Voltage (Vrms)	Output Power (W)	Output Voltage (V)	Output Current (A)	Efficiency@ Max Load and 70°C Case (%)	Max. Case Temp. (°C)	Input Current (Arms)	Max. Input Power (W)	THD @ Max. Load	Power Factor @ Max. Load	Surge Protection Common/Diff (KV)	Envir. Protection Rating
120	300	80 ~ 280	0.10 – 1.5	91%	80°C	2.73	330	<20%	>0.95	4/4	UL Dry & Damp, Type HL
230				93%		1.42					
277				93%		1.21					

Enclosure

	In. (mm)
Case Length	8.33 (211.5)
Case Width	4.46 (113.3)
Case Height	1.44 (36.6)
Mounting Length	8.84 (224.6)
Mounting Width	4.54 (115.3)
Overall Length	9.47 (240.5)


Wiring Diagram



Input and output use lead-wires.
Lead-wires are 18AWG 105C/600V solid copper.

Lead Length

Standard Lead Length is 275 mm (±30mm) on all wires outside the can.



Dimming Method	Dimming Range		Other Comments
1-10V Isolated	10% ~ 100%		Dimming source current: 150 µA (±3%)
DALI	1 ~ 254	10% ~ 100%	Linear or Logarithmic Variation
Amp Dimming	30% ~ 100%		Linear
AOC range	0.35A to 1.5A		

Xitanium 300W 120-277V 0.10-1.50A Programmable

Features

- 50,000+ hour lifetime¹
- High power design
- Programmable

Benefits

- Enables long life luminaire designs
- Allows for fewer drivers in high power luminaires
- Allows customization of the driver operation through multiple dimming protocols and performance interfaces

Application

- Area
- Roadway
- Floodlights

Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

Product Data

Order Information	
Order Code	929000712703M (Mid-Pack, 4pcs/Box)
Input Information	
Min. Mains Voltage Operational	108V
Max. Mains Voltage Operational	305V
Line Frequency	50/60 Hz
Earth leakage current	<=0.7ma peak (IEC 61347 -1:2007 (Second edition)+A1:2010+A2:2012) <=0.75ma rms (per UL 8750)
Output Information	
Maximum Open Circuit Voltage	380Vdc
Output Current Ripple (ripple = peak to average / average)	15% max @ max lout Low frequency (≤120 Hz) content <5%
Output Current Tolerance (In the performance window)	<5%
Protections	Short Circuit, Open Circuit Protection for LED + and LED – and Temperature Foldback
Features	
Dimming	0-10V, DALI, AmpDim and Integrated Dynadimmer
AOC (Adjustable Output Current)	Programmed via DALI
CLO (Constant Light Output)	Programmed via DALI
MTP (Module Temperature Protection)	Current cutback to 10% (Refer to specifications below)
Environment & Approbation	
Operating Ambient Temp. Range	-40°C to +55°C
Max Case Temperature (Tcase)	80°C
Agency Approbations	UL8750, IEC 61347 -1:2007 (Second edition)+A1:2010+A2:2012, CSA C22.2 No. 107.1
Electromagnetic Compliance	FCC 47 CFR Part 15 Class A, CISPR 15
Audible Noise	<24dB Class A
Weight	3.6 Lbs / 1.6 kgs

1. Philips Advance Xitanium LED Drivers are designed and manufactured to engineering standards correlating to an average life expectancy of 50,000 hours of operation at maximum rated case temperature.

Xitanium 300W 120-277V 0.10-1.50A Programmable

Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

0-10V Dimming Curve:


Dimming source current from the driver: 150µA (±3%) (@ 0<Vdim<8V)

LED Current Tolerance at any value of Vdim: ± 5% of Imax

Minimum Dim Level: 10% or 100mA if output current is set to less than 1000mA by AOC


Approved Dimmer List

Manufacturer	Manufacturer Part Number
Lutron	Visit www.lutron.com/advance for a list of dimmers (Mark VII) that will work with sthis driver
Leviton	IllumaTech IP7 series
Philips	Sunrise - SR1200ZTUNV



AmpDim Dimming Curve

Parameter	Min	Max	Increments
Start Voltage	170Vrms	250Vrms	1Vrms(configurable by software)
Stop Voltage	150Vrms	230Vrms	1Vrms(configurable by software)
Start Percentage	30%	100%	1%(configurable by software)
Stop Percentage	30%	100%	1%(configurable by software)



Xitanium 300W 120-277V 0.10-1.50A Programmable

Electrical Specifications


All the specifications are typical and at 25°C Tcase unless specified otherwise.

Module Thermal Protection

Factory default: MTP enabled

Philips LED Light Engine option enabled

MTP Option	Default Programmed Values	Dimming Range
Philips LED Light Engine	MTP start dim: 2263 ohms MTP stop dim: 1757 ohms	100% to 10%
Custom: Enter Selected NTC Value and B-Constant(25-85°C)		100% to 10%
NTC1 Preset: 10k NTC Murata: NCP18XH103J03RB		100% to 10%
NTC2 Preset: 15k NTC+390ohms Murata: NCP15XW153E03RC		100% to 10%




Xitanium 300W 120-277V 0.10-1.50A Programmable

Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

Operating Window





Xitanium 300W 120-277V 0.10-1.50A Programmable

Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

Efficiency





Xitanium 300W 120-277V 0.10-1.50A Programmable

Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

Efficiency





Xitanium 300W 120-277V 0.10-1.50A Programmable

Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

Efficiency




Xitanium 300W 120-277V 0.10-1.50A Programmable


Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

Output Current vs. Driver Case Temperature





Driver Lifetime vs. Driver Case Temperature



Xitanium 300W 120-277V 0.10-1.50A Programmable


Performance Characteristics

Based on measurements on a typical sample. The accuracy of the measurements is within the tolerance of the measurement instruments. The graphs are meant to be a guideline and not a specification.



Xitanium 300W 120-277V 0.10-1.50A Programmable

Inrush Current Info



V _{in}	I _{peak}	T (@ 10% of I _{peak})
120 Vrms	77A	440µs
230 Vrms	138A	520µs
277 Vrms	166A	530µs

Inrush current is measured at peak of the corresponding line voltage, source impedance per NEMA 410.

Lightning Surge Info

ANSI Surge Type	Differential Mode (L-N)	Common Mode (L-G, N-G, L&N-G)
1.2/50µs Combination Wave (w/t 2Ω)	4kV	4kV

Programming Tool

Philips MultiOne

For latest version please check www.philips.com/multione

CE Isolation

Basic Isolation: 2U+1000V

Double Isolation: 4U+2750V

Isolation	Input Wires	Output Wires	DALI Wires	0-10V Wires	Chassis
Input Wires	NA	Basic	Basic	Basic	Double
Output Wires	Basic	NA	Basic	Basic	Basic
DALI Wires	Basic	Basic	NA	NA	Double
0-10V Wires	Basic	Basic	NA	NA	Double
Chassis	Double	Basic	Double	Double	NA

UL Isolation

Isolation	Input Wires	Output Wires	DALI Wires (Class 1&2)	0-10V Wires (Class 1&2)	Chassis
Input Wires	NA	2xU+1kV	2.5kVac	2.5kVac	2xU+1kV
Output Wires	2xU+1kV	NA	2.5kVac	2.5kVac	2xU+1kV
DALI Wires (Class 1&2)	2.5kVac	2.5kVac	NA	NA	2.5kVac
0-10V Wires (Class 1&2)	2.5kVac	2.5kVac	NA	NA	2.5kVac
Chassis	2xU+1kV	2xU+1kV	2.5kVac	2.5kVac	NA

U = Max input voltage

UL Conditions of Acceptability

Please contact your Philips representative for a copy of the latest UL Conditions of Acceptability (COA).

© 2015 Koninklijke Philips N.V. All rights reserved.
Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.
philips.com/leddrivers



Philips Lighting North America Corporation
10275 W. Higgins Road, Rosemont IL 60018
Tel: 800-322-2086 Fax: 888-423-1882
Customer/Technical Service: 800-372-3331
OEM Support: 866-915-5886

Imported by: Philips Lighting
A division of Philips Electronics Ltd.
281 Hillmount Rd, Markham, ON, Canada L6C 2S3
Tel. 800-668-9008