


## 1 x TLED 14.5W 4000K 165D 92900028

1 x 1600 lm

Polar intensity diagram




Light output ratio 1.00  
Service upward 0.15  
Service downward 0.85

CIE flux code 38 66 87 85 100

UGRcen (4Hx8H, 0.25H) 24

Quantity estimation diagram




Utilisation factor table

Room Index k	Reflectances (%) for ceiling, walls and working plane (CIE)											
	0.80				0.70				0.50			
	0.80	0.80	0.70	0.70	0.70	0.70	0.50	0.50	0.30	0.30	0.00	0.00
0.60	0.42	0.40	0.41	0.40	0.39	0.31	0.30	0.25	0.28	0.24	0.21	0.21
0.80	0.52	0.49	0.50	0.48	0.47	0.39	0.37	0.32	0.35	0.31	0.27	0.27
1.00	0.60	0.55	0.57	0.56	0.54	0.46	0.44	0.38	0.41	0.37	0.33	0.33
1.25	0.68	0.62	0.65	0.62	0.60	0.53	0.50	0.45	0.47	0.43	0.38	0.38
1.50	0.74	0.67	0.71	0.68	0.65	0.58	0.55	0.50	0.52	0.47	0.43	0.43
2.00	0.84	0.75	0.80	0.76	0.72	0.66	0.62	0.58	0.59	0.55	0.50	0.50
2.50	0.90	0.80	0.86	0.81	0.77	0.71	0.68	0.63	0.64	0.60	0.55	0.55
3.00	0.95	0.83	0.91	0.85	0.81	0.76	0.72	0.68	0.68	0.64	0.59	0.59
4.00	1.02	0.88	0.97	0.91	0.85	0.81	0.77	0.73	0.73	0.70	0.64	0.64
5.00	1.06	0.91	1.01	0.94	0.88	0.84	0.80	0.77	0.76	0.73	0.67	0.67

Ceiling mounted

UGR diagram



Luminance Table

Plane Cone	0.0	15.0	30.0	45.0	60.0	75.0	90.0
45.0	9942	8131	7149	6685	6452	6359	6400
50.0	9674	7710	6734	6328	6131	6064	6121
55.0	9336	7250	6311	5979	5828	5790	5864
60.0	8911	6739	5879	5650	5549	5542	5632
65.0	8344	6170	5442	5339	5289	5311	5419
70.0	7581	5547	5011	5046	5050	5102	5224
75.0	6519	4847	4579	4779	4831	4912	5052
80.0	5016	4115	4179	4539	4640	4747	4900
85.0	2758	3424	3842	4342	4479	4604	4770
90.0	676	3092	3606	4192	4353	4492	4669

(cd/m²)

SL10662-TL

2013-08-02