

Make the move to **CorePro LED**



5" unit shown with standard (E26) adapter to fit medium base sockets

Features

- 4", 5", & 6" apertures
- Efficacy: 63-89 lm/w¹
- CCT: 3000 K & 4000 K
- CRI: 80 & 90 min.
- Lumens: 750-1250¹
- Wattage: 11W-16W
- Voltage: 120V (50/60 Hz)
- Dimming to 10% (TRIAC)
- 50,000 hour rated life (L70)
- Suitable for wet locations
- ENERGY STAR® certified and meets Title-24 requirements
- Standard 5 year limited warranty³
- Standard incandescent Socket Adapter included with each trim²
- IC/Airseal New Construction and IC/Airseal Remodeler frame-in kit

1. See the ordering guides in this brochure and the CP4, CP5, and CP6 spec sheets for complete listing of lumen packages available per configuration.

2. See spec sheets for list of popular compatible housings for retrofit applications.

3. See Philips.com/warranties for more on Philips Lightolier's standard 5-year limited warranty.





© 2016 Philips Lighting Holding B.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

PLi-1419TF 02/16 philips.com/luminares

Philips Lighting
North America
Corporation
200 Franklin Square Drive
Somerset, NJ 08873
Tel. 855-486-221

Philips Lighting Canada Ltd.
281 Hillmount Rd,
Markham, ON,
Canada L6C 2S3
Tel. 800-668-9008

**PHILIPS
LIGHTOLIER**



Downlighting

CorePro LED




Less money
Bigger impact

Affordable 4", 5", and 6" downlight solutions

Philips Lightolier CorePro downlights are a family of low cost, LED recessed downlights that meet ENERGY STAR® and Title-24 compliance for residential and light commercial spaces. The new family's complete offering of an IC/Airseal remodeler and IC/Airseal new construction frame-in kit allows CorePro to be used beyond retrofit applications.

CorePro LED 4" downlight



CP4RB07830W

- Lumens: 800
- CCT: 3000K
- CRI: 80
- Efficacy: 73 lm/w
- Max. Watts: 11W
- Voltage: 120V
- Listing: Wet

CP4RB07930W

- Lumens: 750
- CCT: 3000K
- CRI: 90
- Efficacy: 68 lm/w
- Max. Watts: 11W
- Voltage: 120V
- Listing: Wet

CP4RB07840W

- Lumens: 850
- CCT: 4000K
- CRI: 80
- Efficacy: 77 lm/w
- Max. Watts: 11W
- Voltage: 120V
- Listing: Wet

Frames




Catalog Number Description

- | | |
|-------|--|
| CP4RN | 4" New Construction IC/Airseal frame-in kit with LED Connector |
| CP4RR | 4" Remodeler IC/Airseal frame-in kit with LED Connector |

- Architecturally-pleasing white baffle trim design
- Great visual comfort while delivering high lumen output
- Three apertures and ten configurations to choose from
- Wet location listing for shower light applications
- Flexible springs allow for tool-less trim installation
- Compatible with many Philips Lightolier and competitive housings (*see spec sheets for list of popular compatible housings*)

CorePro LED 5" downlight



CP5RB08830W

- Lumens: 950
- CCT: 3000K
- CRI: 80
- Efficacy: 73 lm/w
- Max. Watts: 13W
- Voltage: 120V
- Listing: Wet

CP5RB08930W

- Lumens: 900
- CCT: 3000K
- CRI: 90
- Efficacy: 69 lm/w
- Max. Watts: 13W
- Voltage: 120V
- Listing: Wet

CP5RB08840W

- Lumens: 1000
- CCT: 4000K
- CRI: 80
- Efficacy: 77 lm/w
- Max. Watts: 13W
- Voltage: 120V
- Listing: Wet




Catalog Number Description

- | | |
|-------|--|
| CP5RN | 5" New Construction IC/Airseal frame-in kit with LED Connector |
| CP5RR | 5" Remodeler IC/Airseal frame-in kit with LED Connector |



Visit philips.com/warranties for more information on the standard 5-year limited warranty.

CorePro LED 6" downlight



CP6RB07830W

- Lumens: 835
- CCT: 3000K
- CRI: 80
- Efficacy: 75 lm/w
- Max. Watts: 11W
- Voltage: 120V
- Listing: Wet

CP6RB10930W

- Lumens: 1000
- CCT: 3000K
- CRI: 90
- Efficacy: 63 lm/w
- Max. Watts: 16W
- Voltage: 120V
- Listing: Wet

CP6RB10830W

- Lumens: 1200
- CCT: 3000K
- CRI: 80
- Efficacy: 86 lm/w
- Max. Watts: 14W
- Voltage: 120V
- Listing: Wet

CP6RB10840W

- Lumens: 1250
- CCT: 4000K
- CRI: 80
- Efficacy: 89 lm/w
- Max. Watts: 14W
- Voltage: 120V
- Listing: Wet



Catalog Number Description

- | | |
|-------|--|
| CP6RN | 6" New Construction IC/Airseal frame-in kit with LED Connector |
| CP6RR | 6" Remodeler IC/Airseal frame-in kit with LED Connector |