

Unlock your vision

VERSAFORM
1'X4' LED PoE



DIRECT, BEAM SHAPING LIGHT GUIDE WITH STEPPED DIFFUSER
CRI >80 4000K, 2300 lm

Project: _____

Spec Type: _____

Catalog No: 4114DxxxP8AG

Qty _____

Line Notes: _____



ACTILUME




Ordering guide

Product Type	Version	Configuration	Light Source *	CRI/CCT	Lumens *	Housing	Wiring	Voltage	Driver
<input type="checkbox"/> 4114	<input type="checkbox"/>	<input type="checkbox"/> ST	<input type="checkbox"/> P	<input type="checkbox"/> 8A	<input type="checkbox"/> G	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
VersaForm 1'x4' LED PoE	D1 Standard T Grid D2 Slot T Grid	ST Standalone	P LED PoE	8C CRI 80 3000K 8B CRI 80 3500K 8A CRI 80 4000K	G 2300 lm	S Standard (22ga.)	7 1 cct w/ Dimming	N Not applicable (Class 2)	E Standard


* Nominal values within a range. Consult ies file for exact color temp, lumens and up/down distribution

Upgrades & Accessories Please indicate with check mark.

Drywall Kit Trim Mount



Drywall Kit
Trim mount detail



Wood Frame **Hanger Wire**
Can be mounted to wood frame or with hanger wire.

Integrated Controls Please indicate with check mark.

Philips Actilume Daylight and Occupancy Sensor (DO)




VERSAFORM

1'X4' LED PoE

DIRECT, BEAM SHAPING LIGHT GUIDE WITH STEPPED DIFFUSER

Photometry



Total Output	2354 lm
Efficacy	113.7 lm/W
CCT	3876K
CRI	83
R9	12
Distribution	0% Up / 100% Down
Spacing Criteria (0/90°)	1.35/1.61

Fixture photometry has been conducted in accordance with IESNA LM-79-08

Lumen maintenance of the LEDs has been tested by the manufacturer in accordance with IESNA LM-80-08

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	668	668	668	668	668	0
5	667	669	672	673	675	64
15	657	668	681	696	701	193
25	634	651	683	718	732	316
35	582	609	652	709	726	410
45	497	526	573	637	653	445
55	380	407	446	505	516	404
65	254	271	297	349	350	302
75	126	144	155	189	191	172
85	27	38	38	50	41	48
90	1	0	0	1	0	0
95	0	0	0	0	0	0
105	0	0	0	0	0	0
115	0	0	0	0	0	0
125	0	0	0	0	0	0
135	0	0	0	0	0	0
145	0	0	0	0	0	0
155	0	0	0	0	0	0
165	0	0	0	0	0	0
175	0	0	0	0	0	0
180	0	0	0	0	0	0

Coefficients of Utilization (%)

RCR	Ceiling: Wall:									
	70		80		70		50		50	
	70	50	30	10	70	50	30	50	30	10
0	119	119	119	119	116	116	116	111	111	111
1	108	103	99	95	106	101	97	97	94	91
2	98	90	83	77	96	88	81	84	79	74
3	89	78	70	63	87	77	69	74	67	62
4	81	69	60	53	79	68	59	65	58	52
5	75	61	52	45	73	60	52	58	50	45
6	69	55	46	39	67	54	45	52	45	39
7	64	50	41	34	62	49	40	47	40	34
8	59	45	36	30	57	44	36	43	36	30
9	55	41	33	27	54	41	33	40	32	27
10	52	38	30	25	50	37	30	36	29	24

Avg. Luminance (cd/m²)

Vertical Angle	Horizontal Angle		
	0	45	90
55	1845	2167	2506
65	1677	1961	2310
75	1354	1670	2053
85	864	1213	1301

Electrical Specifications



Input Voltage	PoE (51-54VDC)
Input Power	20.7W
Tested values – contact technical support for rated values. Standby power <0.9W	

VERSAFORM

1'X4' LED PoE

DIRECT, BEAM SHAPING LIGHT GUIDE WITH STEPPED DIFFUSER

Options and Details




Mounting



D1 Standard T-Grid

Option D1 works with 9/16" and 15/16" flat T-grid ceilings. It can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.



D2 Slot T-Grid

Option D2 is designed to sit close to flush with slot T-grid ceilings and some tegular tile ceiling types.

Housing

Die-formed, post painted, 22 gauge cold-rolled steel. Wire entrance with additional knock-out available on top side for electrical connections.

Weight

Maximum: 2x2 = 24lb, 1x4 = 28lb, 2x4 = 38lb

Optical System

The optical frame assembly consists of integrated LED arrays edgelighting a light guide panel in order to deliver uniform controlled light through a lower lens. The optical frame ends are constructed from die-formed cold-rolled steel, assembled together with extruded aluminum profiles in a sturdy frame. The frame is hinged (side marked) to allow easy access to the inside of the fixture. Maintenance can be performed from below the ceiling.

Driver

Philips PoE Lighting Controller:

Lumen Maintenance

At an ambient temperature of 25°C, the LED lumen maintenance expectation is L₇₀ (9k) > 54 kh. Reported according to IES TM-21 Addendum A methodology (9k LM-80 test duration)

Mounting

Fixtures can be fastened directly to the T-bar grid and/or tied-off to the building structure.

Electrical

Wire Access Cover provides RJ45 connection point for PoE network.

Approvals

Certified to UL, CSA, DLC & IES Standards. City of Chicago Approved CCEA (housing option C).

Finish

Housing and Frame painted, high quality, powder coated matte white only.

Environment

Rated for dry & damp locations in operating in ambient temperatures of 25°C. Certain luminaire components may be adversely affected by contaminants. Damage caused by sulfur, chlorine, petroleum based solutions or other contaminants are not covered under warranty.

Due to continuing product improvements, Philips Ledalite reserves the right to change the specifications without notice.



© 2014 Koninklijke Philips N.V. All rights reserved. Specifications are subject to change without notice. www.philips.com/luminaires

VrsFrm1x4P_8-40K23Im.pdf 07.15 page 3 of 3

Philips Lighting
North America Corporation
200 Franklin Square Drive
Somerset, NJ 08873
Phone: 855-486-2216

Philips Lighting Company
281 Hillmount Road
Markham ON, Canada L6C 2S3
Phone: 800-668-900