

Unlock your vision

VERSAFORM
2'X2' LED PoE



DIRECT, BEAM SHAPING LIGHT GUIDE WITH STEPPED DIFFUSER
CRI >80 3000K, 2300 lm

Project: _____

Spec Type: _____

Catalog No: 4122DxxxP8CG

Qty _____

Line Notes: _____



ACTILUME




Ordering guide

Product Type	Version	Configuration	Light Source *	CRI/CCT	Lumens *	Housing	Wiring	Voltage	Driver
<input type="checkbox"/> 4122	<input type="checkbox"/>	<input type="checkbox"/> ST	<input type="checkbox"/> P	<input type="checkbox"/> 8C	<input type="checkbox"/> G	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
VersaForm 2'x2' LED PoE	D1 Standard T Grid D2 Slot T Grid	ST Standalone	P LED PoE	8C CRI 80 3000K 8B CRI 80 3500K 8A CRI 80 4000K	G 2300 lm	S Standard (22ga.)	7 1 cct w/ Dimming	N Not applicable (Class 2)	E Standard


* Nominal values within a range. Consult ies file for exact color temp, lumens and up/down distribution

Upgrades & Accessories Please indicate with check mark.

Drywall Kit Trim Mount



Drywall Kit
Trim mount detail



Wood Frame **Hanger Wire**
Can be mounted to wood frame or with hanger wire.

Integrated Controls Please indicate with check mark.

Philips Actilume Daylight and Occupancy Sensor (DO)




VERSAFORM

2'X2' LED PoE

DIRECT, BEAM SHAPING LIGHT GUIDE WITH STEPPED DIFFUSER

Photometry



Total Output	2295 lm
Efficacy	107.7 lm/W
CCT	2995K
CRI	81
R9	3
Distribution	0% Up / 100% Down
Spacing Criteria (0/90°)	1.39/1.69

Fixture photometry has been conducted in accordance with IESNA LM-79-08

Lumen maintenance of the LEDs has been tested by the manufacturer in accordance with IESNA LM-80-08

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	630	630	630	630	630	0
5	630	631	634	636	638	61
15	626	633	648	662	670	184
25	611	626	660	695	713	305
35	570	594	643	703	729	405
45	490	525	569	644	667	445
55	371	401	442	509	518	402
65	241	261	285	338	345	293
75	118	133	137	169	179	158
85	28	30	31	47	46	42
90	0	0	0	0	0	0
95	0	0	0	0	0	0
105	0	0	0	0	0	0
115	0	0	0	0	0	0
125	0	0	0	0	0	0
135	0	0	0	0	0	0
145	0	0	0	0	0	0
155	0	0	0	0	0	0
165	0	0	0	0	0	0
175	0	0	0	0	0	0
180	0	0	0	0	0	0

Coefficients of Utilization (%)

RCR	Ceiling: Wall:									
	70		80		70		50		50	
0	119	119	119	119	116	116	116	111	111	111
1	109	104	99	95	106	101	97	97	94	91
2	98	90	83	77	96	88	82	84	79	74
3	89	79	70	63	87	77	69	74	67	62
4	82	69	60	53	79	68	59	65	58	52
5	75	62	52	45	73	60	52	58	51	45
6	69	55	46	39	67	54	45	52	45	39
7	64	50	41	34	62	49	40	47	40	34
8	59	45	36	30	57	44	36	43	36	30
9	55	41	33	27	54	41	33	39	32	27
10	51	38	30	24	50	37	30	36	29	24

Avg. Luminance (cd/m²)

Vertical Angle	Horizontal Angle		
	0	45	90
55	1793	2135	2504
65	1584	1872	2263
75	1269	1470	1922
85	884	990	1459



Electrical Specifications

Input Voltage	PoE (51-54VDC)
Input Power	21.3W
Tested values – contact technical support for rated values. Standby power <0.9W	


VERSAFORM 2'X2' LED PoE

DIRECT, BEAM SHAPING LIGHT GUIDE WITH STEPPED DIFFUSER

Options and Details




Mounting



D1 Standard T-Grid

Option D1 works with 9/16" and 15/16" flat T-grid ceilings. It can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.



D2 Slot T-Grid

Option D2 is designed to sit close to flush with slot T-grid ceilings and some tegular tile ceiling types.

Housing

Die-formed, post painted, 22 gauge cold-rolled steel. Wire entrance with additional knock-out available on top side for electrical connections.

Weight

Maximum: 2x2 = 24lb, 1x4 = 28lb, 2x4 = 38lb

Optical System

The optical frame assembly consists of integrated LED arrays edgelighting a light guide panel in order to deliver uniform controlled light through a lower lens. The optical frame ends are constructed from die-formed cold-rolled steel, assembled together with extruded aluminum profiles in a sturdy frame. The frame is hinged (side marked) to allow easy access to the inside of the fixture. Maintenance can be performed from below the ceiling.

Driver

Philips PoE Lighting Controller.

Lumen Maintenance

At an ambient temperature of 25°C, the LED lumen maintenance expectation is L₇₀ (9k) > 54 kh. Reported according to IES TM-21 Addendum A methodology (9k LM-80 test duration)

Mounting

Fixtures can be fastened directly to the T-bar grid and/or tied-off to the building structure.

Electrical

Wire Access Cover provides RJ45 connection point for PoE network.

Approvals

Certified to UL, CSA, DLC & IES Standards. City of Chicago Approved CCEA (housing option C).

Finish

Housing and Frame painted, high quality, powder coated matte white only.

Environment

Rated for dry & damp locations in operating in ambient temperatures of 25°C. Certain luminaire components may be adversely affected by contaminants. Damage caused by sulfur, chlorine, petroleum based solutions or other contaminants are not covered under warranty.

Due to continuing product improvements, Philips Ledalite reserves the right to change the specifications without notice.



© 2014 Koninklijke Philips N.V. All rights reserved. Specifications are subject to change without notice. www.philips.com/luminaires

VrsFrm2x2P_8-30K23Im.pdf 07.15 page 3 of 3

Philips Lighting
North America Corporation
200 Franklin Square Drive
Somerset, NJ 08873
Phone: 855-486-2216

Philips Lighting Company
281 Hillmount Road
Markham ON, Canada L6C 2S3
Phone: 800-668-900