# Energy saving SIIICONE lamps.



# PHILIPS ENERGY SAVER SILICONE COMPACT FLUORESCENT I AMPS



Philips Energy Saver Silicone compact fluorescent lamps provide worry-free energy savings and reduced operating costs.

# **Energy savings**

 14W saves up to \$40 in energy costs as compared to a 60W incandescent lamp\*

## Long life


Lasts 8,000 hours\*\*

# **Energy saving replacement for incandescent bulbs**

- Shatter Resistent for safety
- Silicone cover contains broken glass for a no mess clean up
- Soft-to-the-Touch
- Provides warm, white light
- Smaller size fits most applications

\*, \*\*, See footnotes on reverse side





# Ordering, Electrical and Technical Data (Subject to change without notice)

| Part Number | Ordering Code      | Nom.<br>Watts | Volts | Lamps<br>per<br>SKU | Lamp<br>Type    | Lamp<br>Base | Rated<br>Avg. Life<br>(Hrs.) <sup>1</sup> | Approx.<br>Lumens <sup>2</sup> | CRI | Color<br>Temp<br>(K) | MOL<br>(in.) | Mercury<br>Max |
|-------------|--------------------|---------------|-------|---------------------|-----------------|--------------|---|--------------------------------|-----|----------------------|--------------|----------------|
| 41503-4     | EL/A T2 SC 14W 6/2 | 14            | 120   | 2                   | Silicone<br>A17 | Medium       | 8000                                      | 800                            | 82  | 2700                 | 4            | 2.0            |
| 41504-2     | EL/A T2 SC 9W 6/2  | 9             | 120   | 2                   | Silicone<br>A17 | Medium       | 8000                                      | 450                            | 82  | 2700                 | 4            | 2.0            |

<sup>1.</sup> Rated average life is the length of operation (in hours) at which point an average footnotes from front: of 50% of the lamps will still be operational and 50% will not.

\* At \$0.11 kWH, this 14-Watt Energy Saver bulb rated at 800 lumens uses \$12.32 of electricity over its 8000 hour life. This is a \$40.48 savings when compared to the \$52.80 required to run a 60-watt incandescent bulb rated at 800 lumens over the same period. Actual savings will vary depending on cost per kWH in your area.

# Shipping Data (Subject to change without notice)

| Product<br>Number | SKU UPC<br>(0-46677) |         | Case<br>Qty. | Case<br>Weight<br>(lbs.) | Case<br>Cube<br>(cu. ft.) | Pallet<br>Qty. | SKUs<br>per<br>Layer | Layers<br>High | SKU<br>Dimensions<br>(W x D x H)<br>(In.) | Case<br>Dimensions<br>(W x D x H)<br>(In.) | Pallet Dimensions (W x D x H) (In.) |
|-------------------|----------------------|---------|--------------|--------------------------|---------------------------|----------------|----------------------|----------------|---|--|-------------------------------------|
| 41503-4           | 41503-7              | 41503-2 | 6            | 2.53                     | 0.66                      | 288            | 72                   | 4              | 8.2 × 2.4 × 7.4                           | 8.9 × 15.7 × 8.1                           | 39.4 × 47.2 × 38.1                  |
| 41504-2           | 41504-4              | 41504-9 | 6            | 0.66                     | 0.154                     | 288            | 72                   | 4              | 8.2 × 2.4 × 7.4                           | 8.9 × 15.7 × 8.1                           | 39.4 × 47.2 × 38.1                  |

### WARNINGS AND CAUTIONS:

Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires weather-protected fixture. Do not use where directly exposed to water. Before replacing, turn off power and let lamp cool to avoid electrical shock or burn. This device complies with Part 18 of the FCC Rules. Not for use in totally enclosed recessed fixtures. Reliable operating temperature range -4°F/-20°C to 140°F/60°C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.



<sup>2.</sup> Approximate lumen output at 40% of lamp rated average ■ ENERGY STAR® Qualified.

<sup>\*\*</sup> Based on 3 hours average usage per day/7 days per week.