Light to go





Things just got easier.
Introducing our new lineup
of lighting essentials —
quick to order, easy on your
wallet and simple to use.

Make your next outdoor lighting choice a brand you can trust. **Make it Philips Lighting**.

philips.com/Lighttogo



Philips knows contractors look for dependability and ease of installation when choosing their lighting – and these LED luminaires were designed with that in mind. Strong and long lasting with solid performance, adding light where you need it is quicker and easier than ever.

Easy outdoor **lighting** solutions,

Look for Philips Light **to go**



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication

PLi-17102LL 09/17 philips.com/Light**togo**

Philips Lighting, North America Corporation 200 Franklin Square Drive, Somerset, NJ 08873 Tel. 855-486-2216 Philips Lighting Canada Ltd. 281 Hillmount Rd, Markham, ON, Canada L6C 2S3







Dusk to Dawn



- · Budget-friendly, high quality area lighting for parking and outdoor
- · LED technology will save up to 68% energy over HID.*
- Enhance the sense of
- Square pole mounting standard, round pole mount adapter included.
- · Durable aluminum construction.
- · Lifetime >54,000 hours.** · 5 year limited warranty.
- 250W PSMH (at 295W) and AL-
- 150-NW-G1 at 147W. **Predicted performance derived from LED manufacturer's data and engineering design estimates, based on IESNA LM-80 methodology.
- · Dusk to Dawn is sturdy, fade and abrasion resistant, built of a one-piece diecast aluminum housing.
- save you up to 70% energy over HID.*

· This LED technology will

- Refracted lens design spreads light evenly to reduce glare significantly.
- · Excellent choice for general areas, where lighting can enhance security.
- $\cdot \ \mathsf{Direct\ mount\ or\ arm\ mount}$ - compatible to retrofit onto existing arms easily.
- · 5 year limited warranty.
- * DTDLED rated 39 input watts is 70% less versus metal halide systems rated 129 input watts.
- · Cost-effective and efficient lighting for parking garages, covered walkways and canopies.

Garage & canopy

- · Slim and compact design.
- · Durable, weather-tight IP65 rated construction with a rugged, UV stabilized, frosted lens.
- Easy install with the integral quick-mount plate, or pendant mount with 3/4" rigid conduit.
- · Great choice for new construction or retrofit installation.
- 5 year limited warranty.
- · Complete family of LED floodlights ideal to illuminate signs, building facades or other dark areas.

General purpose floods

- · Can be mounted on the ground, wall or polemounted.
- · IP66 rated.
- · Discreet, modern design.
- · All 5 sizes arrive fully assembled and ready to install. Three larger sizes have a trunnion mount and the two smaller sizes have a knuckle mount.
- Fade-resistant, textured bronze finish with tempered glass lens that is heat and impact resistant.
- 5 year limited warranty.

ices
W 1H

Philips Catalog Code	Watts	Color Temp	Voltage	Replaces
PDTDLED1C5K120GY3SP	39W	5100K	120V	100W MH

Accessories (order separately): PDTDARMGY3S – Mounting arm with hardware

Philips Catalog Code	Watts	Color Temp	Dist.	Replaces
PGC40-NW-G1-SM-5-8-BZ	37W	4000K	Type 5	70W PSMH
PGC57-NW-G1-SM-5-8-BZ	57W	4000K	Type 5	100W PSMH

Philips Catalog Code	Watts	Color Temp	Mounting	Replaces
PFL20-NW-G1-K-FL-8-BZ	20W	4000K	Knuckle Mount 1/2" NPS male	70W PSMH
PFL40-NW-G1-K-FL-8-BZ	39W	4000K	Knuckle Mount 1/2" NPS male	150W PSMH
PFL80-NW-G1-T-FL-8-BZ	79W	4000K	Trunnion	250W PSMH
PFL150-NW-G1-T-FL-8-BZ	146W	4000K	Trunnion	400W PSMH
PFL300-NW-G1-T-FL-8-BZ	301W	4000K	Trunnion	750W PSMH

Please refer to the specification sheets for additional information and technical data, philips.com/Lighttogo

Low profile wall



- Budget-friendly, discreet fixture for a wide variety of outdoor spaces
- Energy efficient fixture that delivers up to 110 lumens per watt.
- Durable construction of die-cast aluminum with a UV stabilized lens and stainless steel hardware

LWL Wall light



- Quick and easy installation - mounts to a standard 3 1/2 or 4" junction box.
- 3 size options: 15, 30 or 50 watt.
- Slim profile, just over 4
- 5 year limited warranty.
- · Ideal wall mount fixture for doorways, entryways and other poorly lit areas.
- Cost-effective enhanced LED performance means you won't have to sacrifice quality for your budget.
- Strong, one-piece, die-cast aluminum housing with a tough polycarbonate lens.
- Built-in photocell for automatic dusk to dawn lighting allow for even more cost-savings.
- Easy installation, the LWL Wall Light mounts to a standard 4" junction box with a galvanized mounting plate.
- 5 year limited warranty.

Tall wall pack



- · Lightweight, compact and built to last.
- Provides up to 83% energy savings over 70W Metal Halide luminaires.*
- The bronze housing is die cast aluminum and impact resistant polycarbonate, with a frosted lens.
- Rated for temperatures from -40 to 104°.
- · Installation is quick and easy, it mounts to a standard 3 1/2 or 4"

iunction box.

- · Lifetime >100,000 hours.**
- 5 year limited warranty.
- TW20 @ 20W and 70W Metal halide.
- ** Predicted performance derived from LED manufacturer's data and IESNA LM-80 methodology.

Wall pack



- · An easy switch from costly HID fixtures.
- Flexible options choose from 30, 50 and 75 watts in two different sizes.
- The 50 watt Wall pack provides the same illumination as a 100 watt HID fixture, and uses over 50% less energy.*
- · Glass refractor lens design cuts down on
- One-piece die-cast aluminum housing.
- 5 year limited warranty.
- 100W HPS Wall Pack at 115W providing 6100 lumens and 50W WP LED providing 5500 lumens

Easy order. Budget friendly. Job ready.

Philips Catalog Code	Watts	Color Temp	Voltage	Replaces
PPW-15-NW-G1-8-BZ	15W	4000K	120-277V	50W PSMH
PPW-30-NW-G1-8-BZ	30W	4000K	120-277V	70W PSMH
PPW-50-NW-G1-8-BZ	50W	4000K	120-277V	100W PSMH

Philips Catalog Code	Watts	Color Temp	Voltage	Replaces
PLWLLED1C5K120PCBBZ	12W	5000K	120V	100W INC

Philips Catalog Code	Watts	Color Temp	Voltage	Replaces
PTW-20-NW-G1-8-BZ	20W	4000K	120 - 277V	100W INC

Philips Catalog Code	Watts	Color Temp	Voltage	Replaces
PWP-30-NW-G1-8-BZ	30W	4000K	120-277V	70W PSMH
PWP-50-NW-G1-8-BZ	50W	4000K	120-277V	100W PSMH
PWP-75-NW-G1-8-BZ	75W	4000K	120-277V	150-250W PSMH