


1 x TLED8.5W 4000K 160D 9290011181

1 x 1050 lm


Polar intensity diagram



Light output ratio 1.00
Service upward 0.16
Service downward 0.84

CIE flux code 38 66 87 84 100

Quantity estimation diagram



Utilisation factor table

Room Index k	Reflectances (%) for ceiling, walls and working plane (CIE)											
	0.80				0.70				0.50			
	0.80	0.50	0.30	0.10	0.80	0.50	0.30	0.10	0.80	0.50	0.30	0.10
0.60	0.42	0.40	0.40	0.40	0.39	0.31	0.30	0.25	0.28	0.24	0.21	0.21
0.80	0.52	0.48	0.50	0.48	0.47	0.39	0.37	0.32	0.35	0.30	0.27	0.27
1.00	0.60	0.55	0.57	0.55	0.54	0.46	0.43	0.38	0.41	0.36	0.32	0.32
1.25	0.68	0.62	0.65	0.62	0.60	0.52	0.50	0.44	0.47	0.42	0.38	0.38
1.50	0.74	0.67	0.71	0.68	0.65	0.58	0.54	0.49	0.51	0.47	0.42	0.42
2.00	0.83	0.75	0.80	0.76	0.72	0.66	0.62	0.57	0.59	0.55	0.49	0.49
2.50	0.90	0.80	0.86	0.81	0.77	0.71	0.67	0.63	0.64	0.60	0.54	0.54
3.00	0.95	0.83	0.90	0.85	0.81	0.75	0.71	0.67	0.67	0.64	0.58	0.58
4.00	1.01	0.88	0.96	0.90	0.85	0.81	0.76	0.73	0.72	0.69	0.63	0.63
5.00	1.06	0.91	1.00	0.94	0.88	0.84	0.79	0.77	0.75	0.73	0.66	0.66

Ceiling mounted

Luminance Table

Plane Cone	0.0	15.0	30.0	45.0	60.0	75.0	90.0
45.0	4125	4045	4103	4312	4695	5340	6398
50.0	3945	3847	3889	4088	4450	5096	6228
55.0	3781	3659	3682	3864	4193	4822	6011
60.0	3630	3488	3493	3660	3941	4531	5752
65.0	3491	3330	3317	3468	3684	4202	5409
70.0	3274	3123	3123	3295	3428	3842	4976
75.0	3282	3080	3034	3159	3191	3453	4390
80.0	3206	2991	2939	3069	2653	2040	97
85.0	3137	2898	2828	2946	2754	2597	2186
90.0	3077	2814	2727	2835	2640	2472	753

(cd/m²)

SL13940

2014-04-29