



PAR30/PAR20 LED

7PAR20/LED/F25/827-822/E26/GL/DIM 120V

Philips PAR30S LED Single Optic Lamps with AirFlux Technology provide superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.


Product data

| General Information | | Wattage Equivalent | |
|---------------------------------------|------------------------------------|---------------------------------|--|
| Cap-Base | E26 [Single Contact Medium Screw] | Wattage Equivalent | 50 W |
| Nominal Lifetime (Nom) | 25000 h | Starting Time (Nom) | 0.5 s |
| Switching Cycle | 25000X | Warm Up Time To 60% Light (Nom) | 0.5 s |
| Technical Type | 7-50W | Power Factor (Nom) | 0.75 |
| | | Voltage (Nom) | 120 V |
| Light Technical | | Temperature | |
| Color Code | 822-827 [tunable warm white] | T-Case Maximum (Nom) | 82 °C |
| Beam Angle (Nom) | 25 ° | | |
| Luminous Flux (Nom) | 500 lm | Controls and Dimming | |
| Luminous Flux (Rated) (Nom) | 500 lm | Dimmable | Yes |
| Luminous Intensity (Nom) | 1300 cd | | |
| Color Designation | Warm White (WW) | Approval and Application | |
| Rated Beam Angle | 25 ° | Suitable For Accent Lighting | Yes |
| Correlated Color Temperature (Nom) | 2200-2700 K | | |
| Luminous Efficacy (rated) (Nom) | 71.43 lm/W | Product Data | |
| Color Consistency | <6 | Order product name | 7PAR20/LED/F25/827-822/E26/GL/DIM 120V |
| Color Rendering Index (Nom) | 80 | EAN/UPC - Product | 046677471101 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % | Order code | 929001317204 |
| | | Numerator - Quantity Per Pack | 1 |
| | | Numerator - Packs per outer box | 6 |
| | | Material Nr. (12NC) | 929001317204 |
| | | Net Weight (Piece) | 0.135 kg |
| Operating and Electrical | | | |
| Input Frequency | 60 Hz | | |
| Power (Rated) (Nom) | 7 W | | |
| Lamp Current (Nom) | 70 mA | | |

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.
- CAUTION: Risk of electric shock— do not use where directly exposed to water
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.



Dimensional drawing



PAR20 120V 6W-50W 500lm 25D 2700K E26 D

| Product | D | C |
|--|-------|---------|
| 7PAR20/LED/F25/827-822/E26/GL/DIM 120V | 63 mm | 85.5 mm |


Photometric data



LEDspot PAR20 7W 822 827 500lm 25D


PAR30/PAR20 LED

Photometric data




8-50 W GU5.3 /827 MR16

Lifetime



LEDspot PAR20 7W 500lm



LEDspot PAR20 7W 500lm

