

**Ordering Information**

Catalog No.	Finish	Mounting	Lamp
9022WH	Matte White	All Lytespan	55W-150W PAR38
9022BK	Matte Black	Track Systems	(Cool Beam Also) 45W-250W PAR38 (Tungsten-Halogen)

**General Description**

Minimal, functional form with cleanly detailed yoke and ring-shaped lampholder. Front relamping for easy maintenance. Units adjust horizontally up to 350°, vertically up to 90°

**Finish**

All painted finished baked enamel.

**All-In-One-Box**

Product comes with Track Head and Philips LED PAR38 Lamps.

9022LRNFWH White	9022LRFWH White
Come with 9022WH track Head and Philips PAR38 LED Lamp RNF (Narrow Flood)	Come with 9022WH track Head and Philips PAR38 LED Lamp RF (Flood)


**Electrical**

Porcelain socket, medium base, nickel plated screw shell. No 18 braided SF-1 leads with silicone sleeving

**Labels**

UL, I.B.E.W.




Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	



## Lighting Data

### Aiming Angle:

**L** Beam length  
**W** Beam width  
**C** Distance to center of beam  
**D** Distance  
**A** Aiming angle  
**FC** Footcandles  
**L** and **W** are the outer points where the candlepower drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.



LAMP	BEAM SPREAD (To 50% Max CP)	BEAM CTR. C.P. (Candelas)	RATED LIFE (Hours)	0° AIMING ANGLE (A)				30° AIMING ANGLE (A)				45° AIMING ANGLE (A)				60° AIMING ANGLE (A)						
				DIST-ANCE (D)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)	DIST-ANCE (D)	DIST-ANCE (C)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)	DIST-ANCE (D)	DIST-ANCE (C)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)	DIST-ANCE (D)	DIST-ANCE (C)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)
45W PAR38 NSP (T-H)	6°	8,500	2,000	7'	173	0.7'	0.7'	6'	3.5'	153	0.8'	0.7'	4'	4.0'	188	0.8'	0.6'	2'	3.5'	266	0.8'	0.4'
				10'	85	1.0'	1.0'	9'	5.2'	68	1.3'	1.1'	6'	6.0'	83	1.3'	0.9'	3'	5.2'	118	1.3'	0.6'
				13'	50	1.4'	1.4'	12'	6.9'	38	1.7'	1.5'	8'	8.0'	47	1.7'	1.2'	4'	6.9'	66	1.7'	0.8'
45W PAR38 SP (T-H)	14°	4,700	2,000	6'	131	1.5'	1.5'	5'	2.9'	122	1.6'	1.4'	3'	3.0'	185	1.5'	1.0'	2'	3.5'	147	2.1'	1.0'
				8'	73	2.0'	2.0'	7'	4.0'	62	2.3'	2.0'	5'	5.0'	66	2.5'	1.7'	3'	5.2'	65	3.1'	1.5'
				10'	47	2.5'	2.5'	9'	5.2'	38	3.0'	2.6'	7'	7.0'	34	3.5'	2.4'	4'	6.9'	37	4.1'	2.0'
45W PAR38 FL (T-H)	28°	1,700	2,000	3'	189	1.5'	1.5'	3'	1.7'	123	2.0'	1.7'	2'	2.0'	150	2.1'	1.4'	1'	1.7'	213	2.5'	1.0'
				5'	68	2.5'	2.5'	5'	2.9'	44	3.4'	2.9'	3'	3.0'	67	3.2'	2.1'	2'	3.5'	53	4.9'	2.0'
				7'	35	3.5'	3.5'	7'	4.0'	23	4.8'	4.0'	4'	4.0'	38	4.3'	2.8'	3'	5.2'	24	7.4'	3.0'
75W PAR38 SP	12°	5,200	2,000	6'	144	1.3'	1.3'	5'	2.9'	135	1.4'	1.2'	3'	3.0'	204	1.3'	0.9'	2'	3.5'	163	1.7'	0.8'
				8'	81	1.7'	1.7'	7'	4.0'	62	2.3'	2.0'	5'	5.0'	74	2.1'	1.5'	3'	5.2'	72	2.5'	1.3'
				10'	52	2.1'	2.1'	9'	5.2'	42	2.5'	2.2'	7'	7.0'	38	3.0'	2.1'	4'	6.9'	41	3.5'	1.7'
75W PAR38 FL	30°	1,860	2,000	4'	116	2.1'	2.1'	3'	1.7'	134	2.2'	1.9'	3'	3.0'	73	3.5'	2.3'	1'	1.7'	233	2.7'	1.1'
				6'	52	3.2'	3.2'	5'	2.9'	48	3.7'	3.1'	4'	4.0'	41	4.6'	3.0'	2'	3.5'	58	5.5'	2.1'
				8'	29	4.3'	4.3'	7'	4.0'	25	5.1'	4.3'	5'	5.0'	26	5.8'	3.8'	3'	5.2'	26	8.2'	3.2'
90W PAR38 NSP (T-H)	7°	19,000	2,000	10'	190	1.2'	1.2'	8'	4.6'	193	1.3'	1.1'	6'	6.0'	187	1.5'	1.0'	4'	6.9'	148	2.0'	1.0'
				15'	84	1.8'	1.8'	12'	6.9'	86	2.0'	1.7'	9'	9.0'	83	2.2'	1.6'	6'	10.4'	66	3.0'	1.5'
				20'	47	2.4'	2.4'	16'	9.2'	48	2.6'	2.3'	12'	12.0'	47	2.9'	2.1'	8'	13.9'	37	4.0'	2.0'
90W PAR38 SP (T-H)	12°	12,000	2,000	8'	187	1.7'	1.7'	7'	4.0'	159	2.0'	1.7'	5'	5.0'	170	2.1'	1.5'	3'	5.2'	167	2.6'	1.3'
				12'	83	2.5'	2.5'	10'	5.8'	78	2.8'	2.4'	7'	7.0'	87	3.0'	2.1'	4'	6.9'	94	3.5'	1.7'
				16'	47	3.4'	3.4'	13'	7.5'	46	3.7'	3.2'	9'	9.0'	52	3.8'	2.7'	5'	8.7'	60	4.3'	2.1'
90W PAR38 FL (T-H)	30°	4,000	2,000	6'	111	3.2'	3.2'	5'	2.9'	104	3.7'	3.1'	3'	3.0'	157	3.5'	2.3'	2'	3.5'	125	5.5'	2.1'
				8'	62	4.3'	4.3'	7'	4.0'	53	5.1'	4.3'	5'	5.0'	57	5.8'	3.8'	3'	5.2'	56	8.2'	3.2'
				10'	40	5.4'	5.4'	9'	5.2'	32	6.6'	5.6'	7'	7.0'	29	8.1'	5.3'	4'	6.9'	31	10.9'	4.3'
150W PAR38 SP	14°	10,500	2,000	8'	164	2.0'	2.0'	7'	4.0'	139	2.3'	2.0'	5'	5.0'	148	2.5'	1.7'	3'	5.2'	146	3.1'	1.5'
				12'	73	2.9'	2.9'	10'	5.8'	68	3.3'	2.8'	7'	7.0'	76	3.5'	2.4'	4'	6.9'	82	4.1'	2.0'
				16'	41	3.9'	3.9'	13'	7.5'	40	4.3'	3.7'	9'	9.0'	46	4.5'	3.1'	5'	8.7'	53	5.1'	2.5'
150W PAR38 NSP (T-H)	9°	37,500	3,000	10'	375	1.6'	1.6'	8'	4.6'	381	1.7'	1.5'	6'	6.0'	368	1.9'	1.3'	4'	6.9'	293	2.6'	1.3'
				15'	167	2.4'	2.4'	12'	6.9'	169	2.5'	2.2'	9'	9.0'	164	2.9'	2.0'	6'	10.4'	130	3.8'	1.9'
				20'	94	3.1'	3.1'	16'	9.2'	95	3.4'	2.9'	12'	12.0'	92	3.8'	2.7'	8'	13.9'	73	5.1'	2.5'
150W PAR38 SP (T-H)	10°	22,000	3,000	10'	220	1.7'	1.7'	8'	4.6'	223	1.9'	1.6'	6'	6.0'	216	2.1'	1.5'	4'	6.9'	172	2.9'	1.4'
				15'	98	2.6'	2.6'	12'	6.9'	99	2.8'	2.4'	9'	9.0'	96	3.2'	2.2'	6'	10.4'	76	4.3'	2.1'
				20'	55	3.5'	3.5'	16'	9.2'	56	3.7'	3.2'	12'	12.0'	54	4.2'	3.0'	8'	13.9'	43	5.7'	2.8'
150W PAR38 FL	30°	4,000	2,000	6'	111	3.2'	3.2'	5'	2.9'	104	3.7'	3.1'	3'	3.0'	157	3.5'	2.3'	2'	3.5'	125	5.5'	2.1'
				8'	62	4.3'	4.3'	7'	4.0'	53	5.1'	4.3'	5'	5.0'	57	5.8'	3.8'	3'	5.2'	56	8.2'	3.2'
				10'	40	5.4'	5.4'	9'	5.2'	32	6.6'	5.6'	7'	7.0'	29	8.1'	5.3'	4'	6.9'	31	10.9'	4.3'
150W PAR38 FL (T-H)	30°	7,000	3,000	7'	143	3.8'	3.8'	6'	3.5'	126	4.4'	3.7'	4'	4.0'	155	4.6'	3.0'	2'	3.5'	219	5.5'	2.1'
				10'	70	5.4'	5.4'	9'	5.2'	56	6.6'	5.6'	6'	6.0'	69	6.9'	4.5'	3'	5.2'	97	8.2'	3.2'
				13'	41	7.0'	7.0'	12'	6.9'	32	8.8'	7.4'	8'	8.0'	39	9.2'	6.1'	4'	6.9'	55	10.9'	4.3'

(FC) is the initial footcandles at the center of the beam.  
 (L) and (W) are to the point that the candlepower drops to 50% of maximum.

### Job Information Type: