



1 x TLED10.5W 3500K165D 9290011184**1 x 1160 lm****Polar intensity diagram**

Light output ratio 1.00
 Service upward 0.15
 Service downward 0.85


CIE flux code 38 66 87 85 100

UGRcen (4Hx8H, 0.25H) 23

Quantity estimation diagram**Utilisation factor table**

Room Index k	Reflectances (%) for ceiling, walls and working plane (CIE)											
	0.80			0.70			0.50			0.30		
	0.80	0.50	0.30	0.80	0.50	0.30	0.80	0.50	0.30	0.80	0.50	0.30
0.60	0.42	0.40	0.30	0.41	0.40	0.39	0.30	0.25	0.28	0.24	0.21	0.21
0.80	0.52	0.49	0.50	0.50	0.48	0.47	0.37	0.32	0.35	0.31	0.27	0.27
1.00	0.60	0.55	0.57	0.56	0.54	0.46	0.44	0.38	0.41	0.37	0.33	0.33
1.25	0.68	0.62	0.65	0.62	0.60	0.53	0.50	0.45	0.47	0.43	0.38	0.38
1.50	0.74	0.67	0.71	0.68	0.65	0.58	0.55	0.50	0.52	0.47	0.43	0.43
2.00	0.84	0.75	0.80	0.76	0.72	0.66	0.62	0.58	0.59	0.55	0.50	0.50
2.50	0.90	0.80	0.86	0.81	0.77	0.71	0.68	0.63	0.64	0.60	0.55	0.55
3.00	0.95	0.83	0.91	0.85	0.81	0.76	0.72	0.68	0.68	0.64	0.59	0.59
4.00	1.02	0.88	0.97	0.91	0.85	0.81	0.77	0.73	0.73	0.70	0.64	0.64
5.00	1.06	0.91	1.01	0.94	0.88	0.84	0.80	0.77	0.76	0.73	0.67	0.67

Ceiling mounted

UGR diagram**Luminance Table**

Plane Cone	0.0	15.0	30.0	45.0	60.0	75.0	90.0
45.0	4640	4610	4678	4847	5183	5895	7208
50.0	4437	4396	4445	4588	4882	5590	7014
55.0	4252	4198	4225	4335	4575	5256	6768
60.0	4083	4018	4023	4096	4262	4886	6460
65.0	3929	3851	3834	3871	3946	4474	6049
70.0	3787	3699	3661	3659	3633	4022	5497
75.0	3663	3562	3503	3465	3320	3514	4726
80.0	3552	3441	3364	3291	3030	2983	3637
85.0	3458	3338	3247	3148	2786	2482	2000
90.0	3385	3257	3156	3039	2614	2241	497

(cd/m²)

SL10662-TL

2014-04-29