


1 x TLED16.5W 4000K160D 9290002882


1 x 2100 lm

Polar intensity diagram



Light output ratio 1.00  
Service upward 0.16  
Service downward 0.84  
CIE flux code 38 66 87 84 100

Quantity estimation diagram



Utilisation factor table

Room Index k	Reflectances (%) for ceiling, walls and working plane (CIE)											
	0.80 0.80				0.70 0.70				0.50 0.50			
	0.80	0.50	0.30	0.10	0.70	0.50	0.30	0.10	0.50	0.30	0.10	0.00
0.60	0.42	0.40	0.40	0.40	0.39	0.31	0.30	0.25	0.28	0.24	0.21	0.21
0.80	0.52	0.48	0.50	0.48	0.47	0.39	0.37	0.32	0.35	0.30	0.27	0.27
1.00	0.60	0.55	0.57	0.55	0.54	0.46	0.43	0.38	0.41	0.36	0.32	0.32
1.25	0.68	0.62	0.65	0.62	0.60	0.52	0.50	0.44	0.47	0.42	0.38	0.38
1.50	0.74	0.67	0.71	0.68	0.65	0.58	0.54	0.49	0.51	0.47	0.42	0.42
2.00	0.83	0.75	0.80	0.76	0.72	0.66	0.62	0.57	0.59	0.55	0.49	0.49
2.50	0.90	0.80	0.86	0.81	0.77	0.71	0.67	0.63	0.64	0.60	0.54	0.54
3.00	0.95	0.83	0.90	0.85	0.81	0.75	0.71	0.67	0.67	0.64	0.58	0.58
4.00	1.01	0.88	0.96	0.90	0.85	0.81	0.76	0.73	0.72	0.69	0.63	0.63
5.00	1.06	0.91	1.00	0.94	0.88	0.84	0.79	0.77	0.75	0.73	0.66	0.66

Ceiling mounted

Luminance Table

Plane Cone	0.0	15.0	30.0	45.0	60.0	75.0	90.0
45.0	8250	8091	8206	8624	9389	10679	12796
50.0	7891	7693	7779	8176	8900	10192	12455
55.0	7562	7319	7365	7728	8386	9644	12022
60.0	7260	6976	6986	7320	7883	9062	11505
65.0	6983	6659	6634	6937	7368	8403	10819
70.0	6548	6245	6246	6590	6857	7684	9952
75.0	6564	6160	6068	6319	6381	6906	8781
80.0	6411	5982	5879	6138	5305	4079	192
85.0	6274	5797	5657	5892	5508	5194	4373
90.0	6154	5628	5453	5669	5280	4943	1505

(cd/m²)

SL13003

2014-03-03