

Compact Fluorescent Energy Saver 3-Way Twister Lamp

Ideal for table lamps and floor lamps

ENERGY SAVER

Energy saver 3-Way twister

Philips 3-Way Twister Compact Fluorescent Lamp is a new innovative approach to 3-Way lighting.

The ideal light bulb to replace the 50/100/150 Watt incandescent 3-Way in table lamps and floor lamps.

Direct replacement for incandescent bulbs

- Double Helix Technology—utilizes two separate burners to provide three distinctive light levels
- · Light does not flicker
- Settings are low/medium/high
- Save 39/77/116 watts in your 3-Way lamps when you replace a 50/100/150 watt incandescent 3-Way with an 11/23/34 energy saver 3-Way twister
- · Optimized color quality to match incandescent lamps
- · Harp extenders included

Long life

Lasts 9 years*



^{*} Based on an average daily usage of 3—4 hours per day, 7 days per week.

Compact Fluorescent Energy Saver 3-Way Twister Lamp

Ordering, Electrical and Technical Data (Subject to change without notice)

		Approx. Color			Appro	ox.			Rated	Min.	Max.		
Product			Nom.	Incand.		Temp.		Initial	MOL	Diam.	Avg. Life	Starting	Ambient
Number	Description	Volts	Watts	Equiv.	Rase	(Kelvin)	CRI	Lumens ¹	(ln)	(ln)	(Hrs)2	Temp	Temp
					Dusc	(Itciviii)		Edifferis	()	()	(1.11.31)	r cirip.	i citip.

Shipping Data

					Cube				SKU Dimensions (W x D x H)(In.)		Pallet Dimensions (W x D x H)(In.)
21193-8	21193-6	21193-1	6	2.7	.30	1080	180	6	$3.0 \times 3.0 \times 7.5$	9.4 × 6.3 × 7.5	49.0 × 4.01 × 47.6

¹⁾ Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.

WARNINGS AND CAUTIONS: Do not use with dimmers. Some electronic timer and photo sensor switches contain dimming circuitry, so before using such a switch, check with it's manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules. Reliable operating temperature range -10°F/-23°C to 140°F/60°C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

		*	Va .		1					*<	4
Bulb Type	Table/Floor Lamp	Outdoor Postlight	Wall Sconce	Surface Mount	Reading Lamp	Border Lights	Recessed Fixture	Open Hanging	Vanity Strip	Ceiling Fan	Chandelier
Twister	•	•	•	•	•			•			
3-Way											
GU24	•		•	•	•		•	•		•	
Soft White Plus	•	•	•		•	•		•		•	
Reflector Flood							•	•			
Dimmable Reflector Flood							•	•			
Decorative Globe		•						•	•	•	
Decorative Candle		•	•		•					•	•
Outdoor		•				•		•			
Bug-A-Way		•				•		•			
Universal	•	•	•	•	•	•	•	•			
Genie	•	•	•	•	•			•			







Philips Lighting North America Corporation 200 Franklin Square Drive, Somerset, NJ 08873 Tel. 855-486-2216

Philips Lighting Canada Ltd. 281 Hillmount Rd, Markham, ON, Canada L6C 2S3 Tel. 800-668-9008

²⁾ Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life. This product should not be used in a socket that is not suitable for 3-Way type lights.