

A man with dark hair, wearing a light green and white vertically striped shirt and a green tie, is looking down at a tablet computer he is holding. He is in an office environment, with a whiteboard and a blue flag visible in the background. The lighting is bright and even.

PHILIPS

Fluorescent

T5 Systems

The evolution of general lighting



Drive for energy efficiency with T5 systems

For years, T8 lighting has been the standard choice for general-purpose lighting applications. From commercial offices and healthcare facilities to schools and government buildings, they are everywhere. However, rising energy costs, new legislation and the need for improved sustainability have prompted building managers and lighting specifiers to look toward T5 systems for lighting solutions that can deliver improved efficiency without compromising light levels or quality.

Philips is leading the charge with one of the lowest-wattage 25W T5 systems available today.¹



Raising the bar for sustainability

Engineered to optimize energy efficiency and energy savings, Philips 25W T5 systems deliver exceptional lighting performance in any general-purpose application, providing the same light output as 28W systems. (See chart below.)

By pairing Philips Advance Optanium ballasts with Philips Energy Advantage 25W lamps, these systems offer significant advantages over competitive systems. (See chart below.)

- Lower input power (See chart below)
- Highest lumens per watt — average 7 more than the competition²
- Longest life — average 4,000 hours more than the competition²

In addition to helping reduce your energy consumption, the Philips 25W system can support overall sustainability goals and may contribute toward LEED certification.

- Lowest mercury content — one of the least amounts in the industry³
- RoHS-compliant⁴
- Aids in meeting ASHRAE 90.1-2010
- Optanium step-dim ballasts meet California's Title 24 requirements by reducing power to 50%



Lighting System	Mean Lumens ⁵	Rated Average Life ⁶	Mean System Lumens ⁷	System Watts ⁸	System Lumens per Watt
Philips 25W	2,750	40,000	5,225	54	97
Philips 28W	2,750	35,000	5,225	58	90
Competitor 26W ²	2,660	30,000	5,054	56	90
Competitor 28W ²	2,900	36,000	5,510	58	95

The Philips 25W T5 systems also feature long-life lamps (rated average life of 40,000 hours⁹), which can help minimize the frequency of maintenance and reduce your lamp recycling costs.

And these systems may also qualify for utility rebates. Check with your local utility provider for more information.



The confidence of choosing a proven provider

Choosing Philips 25W T5 systems is simply a smart decision. With more than 100 years of industry experience and industry-specific expertise, Philips is leading the way toward a brighter, more sustainable future.

As part of a full, comprehensive lighting portfolio, Philips 25W T5 systems represent the state of the art for general lighting applications from a proven lighting partner. In addition to helping save energy and improve sustainability,¹⁰ having a single point of contact for any support issues related to lamps or ballasts can make life simpler for building managers and lighting specifiers.

These systems also feature up to a 42-month lamp/60-month ballast warranty for greater peace of mind.¹²

Contact your Philips sales representative today to learn more about how Philips 25W T5 systems can make a difference in your world.

Footnotes

1. Based on Philips and competitive data as of July 2012.
2. Based on commercially available published data. As of September 2012.
<http://www.gelighting.com/LightingWeb/na/resources/document-library/>
<http://www.sylvania.com/en-us/tools-and-resources/Pages/product-literature.aspx>
3. 1.4mg of mercury.
4. Restrictions on Hazardous Substances (RoHS) is a European directive (2002/95/EC) designed to limit the content of 6 substances [lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB), and polybrominated diphenyl ethers (PBDE)] in electrical and electronic products. For products used in North America compliance to RoHS is voluntary and self-certified.
5. Mean lumens are the approximate lamp lumen output at 40% of the lamp's rated average life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions.
6. Rated average life is the length of operation (in hours) at which point an average of 50% of a large sample of lamps will still be operational and 50% will not.
7. Two-lamp system with 0.95BF ballast (Mean Lumens x2 x 0.95=Mean System Lumens).
8. Ballast input power operating two lamps at 0.95BF.
9. Average life under engineering data with lamps turned off and restarted once every 12 hours.
10. "Sustainable" refers to the lower energy consumption needed when a dimmable ballast is operating at reduced light output levels, which can lead to lower carbon emissions as compared to a similar fixed output ballast.
11. This fluorescent lamp is better for the environment because of its reduced mercury content. All fluorescent lamps contain mercury for effective operation, however, Philips lamps with ALTO® Lamp Technology average 70% less mercury than the 2001 industry average for fluorescent lamps up to sixty inches which are not TCLP-compliant.
12. View limited warranty at <http://www.usa.lighting.philips.com/support/support/warranty> for details and restrictions.





© 2015 Koninklijke Philips N.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

PLT-1596BR 08/15 philips.com/oemna

Philips Lighting
North America Corporation
10275 W. Higgins Road
Rosemont IL 60018
Tel: 800-322-2086
Fax: 888-423-1882
Customer/Technical Service:
800-372-3331
OEM Support: 866-915-5886

Imported by: Philips Lighting,
A division of Philips Electronics Ltd.
281 Hillmount Rd,
Markham, ON, Canada L6C 2S3
Tel. 800-668-9008